

ANTHEM ADVANCED SL SE



SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Stormfire Sprint
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
GAFFEL	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
BAKDÄMPARE	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
KOMPONENTER	
STYRE	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREPPAR	Giant XC Pro, silicone
STAM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
SADELSTOLPE	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm XL:150mm travel / 30.9 x 395mm
SADEL	Giant Grit SLR
DRIVLINJA	
VÄXLAR	SRAM AXS Pod, 1x12
BAKVÄXEL	SRAM XX SL Eagle Transmission
BROMSAR	SRAM Motive ULT, custom color, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
BROMSSPAKAR	SRAM Motive ULT, custom color
KASSETT	SRAM XS 1299 Eagle Transmission, 10x52
KEDJA	SRAM XX SL Eagle Transmission
VEVPARTI	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	CADEX Max XC WheelSystem, 30mm inner width
NAV	[F] CADEX Max XC, CenterLock [R] CADEX Max XC, 132t ratchet driver, CenterLock
EKRAR	CADEX Max XC carbon
DÄCK	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
EXTRAFUNKTIONER	tubeless prepared, MRP 1x CS chain guide
GRÄNSER	
MAX DÄCKAVSTÅND	2.4"
MAX KEDJERINGSTORLEK	34T

Price: 165 000,00 kr

GEOMETRY

RAM	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Längd sadelrör (mm)	400	420	465	495
Vinkel sadelrör	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°	75,5° 76,0°
Topprörets längd (mm)	576 574	602 600	624 623	651 650
Styrhuvud Längd (mm)	90	95	105	115
Vinkel styrhuvud	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°	66,5° 67,0°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	116 112,2	115,9 112,2	115,9 112,2	115,8 112,2
Hjulbas (mm)	1141 1140	1168 1167	1192 1191	1221 1220
Kedjestagslängd (mm)	437 435	437 435	437 435	437 435
Nedre fäste Drop (mm)	51 45	51 45	52 45	52 45
Stack (mm)	602 599	607 603	616 612	626 622
Reach (mm)	420 425	445 450	465 470	490 495
Stå över höjden (mm)	769 775	764 771	758 763	751 758
Styrets bredd (mm)	780	780	780	780
Stamlängd (mm)	60	70	70	80
Vevlängd (mm)	170	170	175	175

All specifications listed are subject to change without notice.