

# ANTHEM ADVANCED SL SE



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLORS</b>	White/Carbon
<b>FRAME</b>	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
<b>FORK</b>	RockShox Sid Flight Attendant XC, 120mm, Flight Attendant Race Day damper, Boost 15x110, 44mm offset
<b>SHOCK</b>	RockShox SidLuxe Flight Attendant, RL3 damper, Solo Air, 210/50
COMPONENTS	
<b>HANDLEBAR</b>	Giant Integrated XC, composite, 780mm, 9-degree upsweep
<b>GRIPS</b>	Giant XC Pro, silicone
<b>STEM</b>	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm
<b>SEATPOST</b>	RockShox Reverb AXS, pod controller remote S: 125mm travel / 30.9 x 395mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
<b>SADDLE</b>	Giant Grit SLR
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM AXS Pod, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM XX SL Eagle Transmission
<b>BRAKES</b>	SRAM Motive ULT, hydraulic, SRAM HS2 CenterLock rotors [F]180mm, [R]160mm
<b>BRAKE LEVERS</b>	SRAM Motive ULT
<b>CASSETTE</b>	SRAM XS 1299 Eagle Transmission, 10x52
<b>CHAIN</b>	SRAM XX SL Eagle Transmission
<b>CRANKSET</b>	SRAM XX SL Eagle Transmission with Quark power meter 34t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant XCR WheelSystem
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
<b>SPOKES</b>	Carbon
<b>TIRES</b>	Maxxis Aspen 29x2.4, foldable, 120tpi, MaxxSpeed, EXO, tubeless
<b>EXTRAS</b>	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

## GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°	75.5°	76.0°
Top Tube Length (mm)	576	574	602	600	624	623	651	650
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°	66.5°	67.0°
Fork Rake (mm)	44		44		44		44	
Trail (mm)	116	112.2	115.9	112.2	115.9	112.2	115.8	112.2
Wheelbase (mm)	1141	1140	1168	1167	1192	1191	1221	1220
Chain Stay Length (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	51	45	51	45	52	45	52	45
Stack (mm)	602	599	607	603	616	612	626	622
Reach (mm)	420	425	445	450	465	470	490	495
Stand Over Height (mm)	769	775	764	771	758	763	751	758
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	60		70		70		80	
Crank Length (mm)	170		170		175		175	

All specifications listed are subject to change without notice.