

ANTHEM ADVANCED SL SE WORLD CHAMPION FRAMESET





SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	SE World Champion
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle
SHOCK	Fox Float SL Factory, 210/50 with custom "Alan Hatherly" compression tune
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
STEM	Giant Integrated XC Carbon S:60mm, M:70mm, L:70mm, XL:80mm

WHEELS	
EXTRAS	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: £3,999.00

GEOMETRY

FRAME	S		M		L	
	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465	
Seat Tube Angle	75.5° 76.0°		75.5° 76.0°		75.5° 76.0°	
Top Tube Length (mm)	576	574	602	600	624	623
Head Tube Length (mm)	90		95		105	
Head Tube Angle	66.5° 67.0°		66.5° 67.0°		66.5° 67.0°	
Fork Rake (mm)	44		44		44	
Trail (mm)	116 112.2		115.9 112.2		115.9 112.2	
Wheelbase (mm)	1141 1140		1168 1167		1192 1191	
Chain Stay Length (mm)	437 435		437 435		437 435	
Bottom Bracket Drop (mm)	51 45		51 45		52 45	
Stack (mm)	602 599		607 603		616 612	
Reach (mm)	420 425		445 450		465 470	
Stand Over Height (mm)	769 775		764 771		758 763	
Handlebar Width (mm)	780		780		780	
Stem Length (mm)	60		70		70	
Crank Length (mm)	170		170		175	

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.