

# ANTHEM ADVANCED SL SE WORLD CHAMPION FRAMESET



## SPECS

| FRAME      |                                                                                                                                         |
|------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| SIZES      | S, M                                                                                                                                    |
| COLORS     | ブラック                                                                                                                                    |
| FRAME      | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle ※リアエンド型番 : SRAM UDH |
| SHOCK      | Fox Float SL Factory, 210/50                                                                                                            |
| COMPONENTS |                                                                                                                                         |
| HANDLEBAR  | Giant Contact SLR XC Integrated, composite, 780mm, 9-degree Backsweep                                                                   |
| STEM       | Giant Contact SLR XC Integrated, composite, -8-degree, S:60mm, M:70mm                                                                   |

| WHEELS             |                             |
|--------------------|-----------------------------|
| EXTRAS             | コンピューターマウント、MRP chain guide |
| LIMITS             |                             |
| MAX TIRE CLEARANCE | 2.4"                        |
| MAX CHAINRING SIZE | 34T                         |

Price: ¥671,000

## GEOMETRY

| FRAME                    | S             | M             |
|--------------------------|---------------|---------------|
|                          | LOW   HIGH    | LOW   HIGH    |
| Seat Tube Length (mm)    | 400           | 420           |
| Seat Tube Angle          | 75.5°   76.0° | 75.5°   76.0° |
| Top Tube Length (mm)     | 576   574     | 602   600     |
| Head Tube Length (mm)    | 90            | 95            |
| Head Tube Angle          | 66.5°   67.0° | 66.5°   67.0° |
| Fork Rake (mm)           | 44            | 44            |
| Trail (mm)               | 116   112.2   | 115.9   112.2 |
| Wheelbase (mm)           | 1141   1140   | 1168   1167   |
| Chain Stay Length (mm)   | 437   435     | 437   435     |
| Bottom Bracket Drop (mm) | 51   45       | 51   45       |
| Stack (mm)               | 602   599     | 607   603     |
| Reach (mm)               | 420   425     | 445   450     |
| Stand Over Height (mm)   | 769   775     | 764   771     |
| Handlebar Width (mm)     | 780           | 780           |
| Stem Length (mm)         | 60            | 70            |
| Crank Length (mm)        | 170           | 170           |

製品仕様は改良、部品供給上の都合により予告なしに変更する場合があります。あらかじめご了承ください。製品重量は個体差により実際と若干異なる場合がございます。また、Giant Premium Model（カーボンバイクおよびダブルサスペンションMTB）は、GPD(Giant Premium Dealer)のみで販売しております。対象販売店は、[店舗検索](#)にてご確認ください。