

ANTHEM X ADVANCED SL 0

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Mossed Dunité
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 SL Factory, 130mm, GRIP X damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Factory, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
STEM	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
SEATPOST	Fox Transfer NEO, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SADDLE	Giant Grit SLR
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano XTR Di2 SW-M9250, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano XTR Di2 RD-M9250
BRAKES	Shimano XTR BR-M9220, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano XTR BL-9220
CASSETTE	Shimano XTR CS-M9200, 10x51
CHAIN	Shimano XTR CN-M9100
CRANKSET	Shimano XTR FC-M9200, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Shimano XTR

WHEELS	
RIMS	Giant XCR WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Carbon
TIRES	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Suggested Retail Price (CDN): \$11,699.00

FRAME GEOMETRY

FRAME	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	420	465	495
Seat Tube Angle	75.1° 75.5°	75.1° 75.6°	75.1° 75.6°
Top Tube Length (mm)	603 602	625 624	653 651
Head Tube Length (mm)	95	105	115
Head Tube Angle	66.1° 66.5°	66.1° 66.6°	66.1° 66.6°
Fork Rake (mm)	44	44	44
Trail (mm)	119.3 115.6	119.2 115.5	119 115.4
Wheelbase (mm)	1172 1171	1196 1195	1225 1224
Chain Stay Length (mm)	437 435	437 435	437 435
Bottom Bracket Drop (mm)	48 42	48 42	48 42
Stack (mm)	611 607	620 616	629 625
Reach (mm)	440 445	460 465	485 490
Stand Over Height (mm)	770 776	762 769	757 764
Handlebar Width (mm)	780	780	780
Stem Length (mm)	50	60	70
Crank Length (mm)	170	175	175

All prices and specifications are subject to change without notice.