

ANTHEM X ADVANCED SL 0

GIANT



SPECS

TELAIO	
TAGLIE	S, M, L, XL
COLORAZIONI	Mossed Dunitite
TELAIO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORCELLA	Fox 34 SL Factory, 130mm, GRIP X damper, Boost 15x110, 44mm offset
AMMORTIZZATORE	Fox Float SL Factory, 210/50
COMPONENTISTICA	
MANUBRIO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
MANOPOLE	Giant Tactal, lock on
ATTACCO MANUBRIO	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
REGGISSELLA	Fox Transfer NEO, remote S: 125mm travel / 30.9 x 395mm M: 150mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 395mm
SELLA	Giant Grit SLR
PEDALI	N/A
SISTEMA DI TRASMISSIONE	
CAMBIO	Shimano XTR Di2 SW-M9250, 1x12
DERAGLIATORE ANTERIORE	N/A
DERAGLIATORE POSTERIORE	Shimano XTR Di2 RD-M9250
FRENI	Shimano XTR BR-M9220, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
COMANDI FRENO	Shimano XTR BL-9220
PACCO PIGNONI	Shimano XTR CS-M9200, 10x51
CATENA	Shimano XTR CN-M9100
GUARNITURA	Shimano XTR FC-M9200, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
MOVIMENTO CENTRALE	Shimano XTR

RUOTE	
CERCHI	Giant XCR WheelSystem
MOZZI	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
RAGGI	Carbon
COPERTONI	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Prezzo: 10.199,00 €

GEOMETRIA

TELAIO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Lunghezza Tubo Sella (mm)	400		420		465		495	
Angolo Tubo Sella	75,0°	75,5°	75,1°	75,5°	75,1°	75,6°	75,1°	75,6°
Lunghezza Tubo Orizzontale (mm)	577	575	603	602	625	624	653	651
Lunghezza Tubo Sterzo (mm)	90		95		105		115	
Angolo Sterzo	66,0°	66,5°	66,1°	66,5°	66,1°	66,6°	66,1°	66,6°
Rake Forcella (mm)	44		44		44		44	
Avancorsa (mm)	119,5	115,7	119,3	115,6	119,2	115,5	119	115,4
Interasse (mm)	1145	1144	1172	1171	1196	1195	1225	1224
Lunghezza Carro Posteriore (mm)	437	435	437	435	437	435	437	435
Drop Movimento Centrale (mm)	48	42	48	42	48	42	48	42
Stack (mm)	606	602	611	607	620	616	629	625
Reach (mm)	415	420	440	445	460	465	485	490
Altezza stand over (mm)	774	780	770	776	762	769	757	764
Larghezza Manubrio c/c (mm)	780		780		780		780	
Lunghezza Attacco Manubrio (mm)	50		50		60		70	
Lunghezza Pedivella (mm)	170		170		175		175	

Le specifiche tecniche e i colori sono soggette a variazioni senza obbligo di preavviso. Verifica la disponibilità con il tuo rivenditore Giant e Liv di fiducia.