

ANTHEM X ADVANCED SL 1



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Solar Prominence
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORGAFFEL	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
BAGDÆMPER	Fox Float SL Factory, 210/50
KOMponenter	
STYR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GREB / STYRBÅND	Giant Tactal, lock on
FREMPIND	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
SADELPIND	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SADEL	Giant Grit SL
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	SRAM AXS Pod, discrete clamp, 1x12
FORSKIFTER	N/A
BAGSKIFTER	SRAM GX AXS Transmission
BREMSE	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
BREMSEGREB	Shimano Deore XT BL-M8100
KASSETTE	SRAM XS 1275, 10x52
KÆDE	SRAM GX Transmission
KRANKSÆT	SRAM GX Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant XCR WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EGER	Carbon
DÆK	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EKSTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Pris: 55.499,00 kr.

GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sadelrørslængde (mm)	400		420		465		495	
Sadelrørsvinkel	75,0°	75,5°	75,1°	75,5°	75,1°	75,6°	75,1°	75,6°
Overrørslængde (mm)	577	575	603	602	625	624	653	651
Kronrørslængde (mm)	90		95		105		115	
Kronrørsvinkel	66,0°	66,5°	66,1°	66,5°	66,1°	66,6°	66,1°	66,6°
Forgaffel fremspring (rake) (mm)	44		44		44		44	
Sti (mm)	119,5	115,7	119,3	115,6	119,2	115,5	119	115,4
Akselafstand (mm)	1145	1144	1172	1171	1196	1195	1225	1224
Kædestagslængde (mm)	437	435	437	435	437	435	437	435
Krankboks drop (mm)	48	42	48	42	48	42	48	42
Stack (mm)	606	602	611	607	620	616	629	625
Reach (mm)	415	420	440	445	460	465	485	490
Skridthøjde (mm)	774	780	770	776	762	769	757	764
Styrbredde (mm)	780		780		780		780	
Frempindslængde (mm)	50		50		60		70	
Pedalarmslængde (mm)	170		170		175		175	

Alle de anførte specifikationer kan ændres uden varsel.