

ANTHEM X ADVANCED SL 1

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Solar Prominence
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Factory, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
STEM	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
SEATPOST	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SADDLE	Giant Grit SL
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM GX AXS Transmission
BRAKES	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
BRAKE LEVERS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XS 1275, 10x52
CHAIN	SRAM GX Transmission
CRANKSET	SRAM GX Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	Giant XCR WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Carbon
TIRES	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Suggested Retail Price (CDN): \$8,699.00

FRAME GEOMETRY

FRAME	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75.0° 75.5°	75.1° 75.5°	75.1° 75.6°	75.1° 75.6°
Top Tube Length (mm)	577 575	603 602	625 624	653 651
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.0° 66.5°	66.1° 66.5°	66.1° 66.6°	66.1° 66.6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	119.5 115.7	119.3 115.6	119.2 115.5	119 115.4
Wheelbase (mm)	1145 1144	1172 1171	1196 1195	1225 1224
Chain Stay Length (mm)	437 435	437 435	437 435	437 435
Bottom Bracket Drop (mm)	48 42	48 42	48 42	48 42
Stack (mm)	606 602	611 607	620 616	629 625
Reach (mm)	415 420	440 445	460 465	485 490
Stand Over Height (mm)	774 780	770 776	762 769	757 764
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	50	50	60	70
Crank Length (mm)	170	170	175	175

All prices and specifications are subject to change without notice.