

# ANTHEM X ADVANCED SL 1

**GIANT**



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLOURS</b>	Solar Prominence
<b>FRAME</b>	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
<b>FORK</b>	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
<b>SHOCK</b>	Fox Float SL Factory, 210/50
COMPONENTS	
<b>HANDLEBAR</b>	Giant Integrated XC, composite, 780mm, 9-degree upsweep
<b>GRIPS</b>	Giant Tactal, lock on
<b>STEM</b>	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
<b>SEATPOST</b>	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
<b>SADDLE</b>	Giant Grit SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM AXS Pod, discrete clamp, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM GX AXS Transmission
<b>BRAKES</b>	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano Deore XT BL-M8100
<b>CASSETTE</b>	SRAM XS 1275, 10x52
<b>CHAIN</b>	SRAM GX Transmission
<b>CRANKSET</b>	SRAM GX Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant XCR WheelSystem
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
<b>SPOKES</b>	Carbon
<b>TYRES</b>	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
<b>EXTRAS</b>	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

**Price: €7,799.00**

## GEOMETRY

FRAME	S	M	L	XL
	LOW   HIGH	LOW   HIGH	LOW   HIGH	LOW   HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75.0°   75.5°	75.1°   75.5°	75.1°   75.6°	75.1°   75.6°
Top Tube Length (mm)	577   575	603   602	625   624	653   651
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66.0°   66.5°	66.1°   66.5°	66.1°   66.6°	66.1°   66.6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	119.5   115.7	119.3   115.6	119.2   115.5	119   115.4
Wheelbase (mm)	1145   1144	1172   1171	1196   1195	1225   1224
Chain Stay Length (mm)	437   435	437   435	437   435	437   435
Bottom Bracket Drop (mm)	48   42	48   42	48   42	48   42
Stack (mm)	606   602	611   607	620   616	629   625
Reach (mm)	415   420	440   445	460   465	485   490
Stand Over Height (mm)	774   780	770   776	762   769	757   764
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	50	50	60	70
Crank Length (mm)	170	170	175	175

*All specifications listed are subject to change without notice.*