

# ANTHEM X ADVANCED SL 1



## SPECS

FRAME	
<b>SIZES</b>	S, M, L, XL
<b>COLORS</b>	Solar Prominence
<b>FRAME</b>	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
<b>FORK</b>	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
<b>SHOCK</b>	Fox Float SL Factory, 210/50
COMPONENTS	
<b>HANDLEBAR</b>	Giant Integrated XC, composite, 780mm, 9-degree upsweep
<b>GRIPS</b>	Giant Tactal, lock on
<b>STEM</b>	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
<b>SEATPOST</b>	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
<b>SADDLE</b>	Giant Grit SL
<b>PEDALS</b>	N/A
DRIVETRAIN	
<b>SHIFTERS</b>	SRAM AXS Pod, discrete clamp, 1x12
<b>FRONT DERAILLEUR</b>	N/A
<b>REAR DERAILLEUR</b>	SRAM GX AXS Transmission
<b>BRAKES</b>	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
<b>BRAKE LEVERS</b>	Shimano Deore XT BL-M8100
<b>CASSETTE</b>	SRAM XS 1275, 10x52
<b>CHAIN</b>	SRAM GX Transmission
<b>CRANKSET</b>	SRAM GX Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
<b>BOTTOM BRACKET</b>	SRAM DUB, press fit

WHEELS	
<b>RIMS</b>	Giant XCR WheelSystem
<b>HUBS</b>	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
<b>SPOKES</b>	Carbon
<b>TIRES</b>	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
<b>EXTRAS</b>	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

**Recommended Retail Price: \$8,000.00**

## GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (inch)	15.7	16.5	18.3	19.5				
Seat Tube Angle	75.0°   75.5°	75.1°   75.5°	75.1°   75.6°	75.1°   75.6°				
Top Tube Length (inch)	22.7   22.6	23.7   23.7	24.6   24.6	25.7   25.6				
Head Tube Length (inch)	3.5	3.7	4.1	4.5				
Head Tube Angle	66.0°   66.5°	66.1°   66.5°	66.1°   66.6°	66.1°   66.6°				
Fork Rake (inch)	1.7	1.7	1.7	1.7				
Trail (inch)	4.7   4.5	4.7   4.5	4.7   4.5	4.7   4.5				
Wheelbase (inch)	45.1   45	46.1   46.1	47.1   47	48.2   48.2				
Chain Stay Length (inch)	17.2   17.1	17.2   17.1	17.2   17.1	17.2   17.1				
Bottom Bracket Drop (inch)	1.9   1.7	1.9   1.7	1.9   1.7	1.9   1.7				
Stack (inch)	23.9   23.7	24.1   23.9	24.4   24.3	24.8   24.6				
Reach (inch)	16.3   16.5	17.3   17.5	18.1   18.3	19.1   19.3				
Stand Over Height (inch)	30.5   30.7	30.3   30.6	30   30.3	29.8   30.1				
Handlebar Width (inch)	30.7	30.7	30.7	30.7				
Stem Length (inch)	2	2	2.4	2.8				
Crank Length (inch)	6.7	6.7	6.9	6.9				

*\*All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*