

ANTHEM X ADVANCED SL 1



TEKNISET TIEDOT

RUNKO	
KOOT	S, M, L, XL
VÄRIT	Solar Prominence
RUNKO	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
HAARUKKA	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
ISKUNVAIMENNIN	Fox Float SL Factory, 210/50
KOMONENTIT	
OHJAUSTANKO	Giant Integrated XC, composite, 780mm, 9-degree upsweep
GRIPIT	Giant Tactal, lock on
OHJAINKANNATIN	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
SATULATOLPPA	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SATULA	Giant Grit SL
POLKIMET	N/A
VOIMANSIIRTO	
VAIHDEVIPU	SRAM AXS Pod, discrete clamp, 1x12
ETUVAIHTAJA	N/A
TAKAVAIHTAJA	SRAM GX AXS Transmission
JARRUT	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
JARRUKAHVAT	Shimano Deore XT BL-M8100
RATASPAKKA	SRAM XS 1275, 10x52
KETJUT	SRAM GX Transmission
KAMPISARJA	SRAM GX Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KESKIÖ	SRAM DUB, press fit

RENKAAT	
VANTEET	Giant XCR WheelSystem
NAVAT	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
PINNAT	Carbon
RENKAAT	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
LISÄTIEDOT	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Suositusuhinta: 7 439,00 €

GEOMETRIA

RUNKO	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Satulaputken pituus (mm)	400		420		465		495	
Satulaputken kulma	75,0°	75,5°	75,1°	75,5°	75,1°	75,6°	75,1°	75,6°
Vaakaputken pituus (mm)	577	575	603	602	625	624	653	651
Emäputken pituus (mm)	90		95		105		115	
Emäputken kulma	66,0°	66,5°	66,1°	66,5°	66,1°	66,6°	66,1°	66,6°
Haarukan offset (mm)	44		44		44		44	
Trail-mitta (mm)	119,5	115,7	119,3	115,6	119,2	115,5	119	115,4
Akseliväli (mm)	1145	1144	1172	1171	1196	1195	1225	1224
Takahaarukan alaputken pituus (mm)	437	435	437	435	437	435	437	435
Keskiön pudotus (mm)	48	42	48	42	48	42	48	42
Stack-mitta (mm)	606	602	611	607	620	616	629	625
Reach-mitta (mm)	415	420	440	445	460	465	485	490
Standover-mitta (mm)	774	780	770	776	762	769	757	764
Ohjaustangon leveys (mm)	780		780		780		780	
Ohjainkannattimen pituus (mm)	50		50		60		70	
Kammen pituus (mm)	170		170		175		175	

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.