

ANTHEM X ADVANCED SL 1



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Solar Prominence
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
VOORVORK	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
DEMPER	Fox Float SL Factory, 210/50
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
HANDVATTEN	Giant Tactal, lock on
STUURPEN	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
ZADELPEN	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
ZADEL	Giant Grit SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM GX AXS Transmission
REMMEN	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
REMHENDELS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XS 1275, 10x52
AANDRIJVING	SRAM GX Transmission
CRANKSET	SRAM GX Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant XCR WheelSystem
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPAKEN	Carbon
BANDEN	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRA'S	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 6.999,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis Lengte (mm)	400		420		465		495	
Zitbuis Hoek	75,0° 75,5°		75,1° 75,5°		75,1° 75,6°		75,1° 75,6°	
Frame Lengte (horizontaal) (mm)	577 575		603 602		625 624		653 651	
Balhoofdbuis Lengte (mm)	90		95		105		115	
Balhoofdbuis Hoek	66,0° 66,5°		66,1° 66,5°		66,1° 66,6°		66,1° 66,6°	
Vork Sprong (mm)	44		44		44		44	
Naloop (mm)	119,5 115,7		119,3 115,6		119,2 115,5		119 115,4	
Wielbasis (mm)	1145 1144		1172 1171		1196 1195		1225 1224	
Liggende achtervork lengte (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	48 42		48 42		48 42		48 42	
Stack (mm)	606 602		611 607		620 616		629 625	
Reach (mm)	415 420		440 445		460 465		485 490	
Stand Over Height (mm)	774 780		770 776		762 769		757 764	
Stuur breedte (mm)	780		780		780		780	
Stuurpen Lengte (mm)	50		50		60		70	
Cranklengte (mm)	170		170		175		175	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.