ANTHEM X ADVANCED SL 1

SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Solar Prominence
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
VOORVORK	Fox 34 SL Performance Elite, 130mm, GRIP X damper, Boost 15x110, 44mm offset
DEMPER	Fox Float SL Factory, 210/50
ONDERDELEN	
STUUR	Giant Integrated XC, composite, 780mm, 9-degree upsweep
HANDVATTEN	Giant Tactal, lock on
STUURPEN	Giant Integrated XC Carbon S:50mm, M:50mm, L:60mm, XL:70mm
ZADELPEN	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
ZADEL	Giant Grit SL
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM AXS Pod, discrete clamp, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM GX AXS Transmission
REMMEN	Shimano Deore XT BR-M8120, hydraulic, Shimano RT-MT905 rotors [F]203mm, [R]180mm
REMHENDELS	Shimano Deore XT BL-M8100
CASSETTE	SRAM XS 1275, 10x52
AANDRIJVING	SRAM GX Transmission
CRANKSET	SRAM GX Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant XCR WheelSystem
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPAKEN	Carbon
BANDEN	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRA'S	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 6.999,00

GEOMETRIE

FRAME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Zitbuis Lengte (mm)	400	420	465	495
Zitbuis Hoek	75,0° | 75,5°	75,1° | 75,5°	75,1° | 75,6°	75,1° | 75,6°
Frame Lengte (horizontaal) (mm)	577 | 575	603 | 602	625 | 624	653 | 651
Balhoofdbuis Lengte (mm)	90	95	105	115
Balhoofdbuis Hoek	66,0° | 66,5°	66,1° | 66,5°	66,1° | 66,6°	66,1° | 66,6°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	119,5 | 115,7	119,3 | 115,6	119,2 | 115,5	119 | 115,4
Wielbasis (mm)	1145 | 1144	1172 | 1171	1196 | 1195	1225 | 1224
Liggende achtervork lengte (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	48 | 42	48 | 42	48 | 42	48 | 42
Stack (mm)	606 | 602	611 | 607	620 | 616	629 | 625
Reach (mm)	415 | 420	440 | 445	460 | 465	485 | 490
Stand Over Height (mm)	774 | 780	770 | 776	762 | 769	757 | 764
Stuur breedte (mm)	780	780	780	780
Stuurpen Lengte (mm)	50	50	60	70
Cranklengte (mm)	170	170	175	175

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.