

# ANTHEM X ADVANCED SL 2

GIANT



## СПЕЦИФИКАЦИИ

РАМКА	
РАЗМЕР	S, M, L, XL
ЦВЯТ	Dark Jungle
РАМКА	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
ВИЛКА	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
ЗАДЕН АМОРТИСЬОР	Fox Float SL Performance, 210/50
КОМПОНЕНТИ	
КОРМИЛО	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
ГРИПОВЕ	Giant Tactal, lock on
ЛАПА	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
КОЛЧЕ ЗА СЕДАЛКА	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
СЕДАЛКА	Giant Grit
ПЕДАЛИ	N/A
DRIVETRAIN	
КОМАНДИ	SRAM Eagle 90 mechanical, 1x12
ПРЕДЕН ДЕРАЙЛЪОР	N/A
ЗАДЕН ДЕРАЙЛЪОР	SRAM Eagle 90 Transmission
СПИРАЧКИ	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
РЪКОХВАТКИ ЗА СПИРАЧКИ	Shimano SLX BL-M7100
КАСЕТА	SRAM 70 1270, 10x52
ВЕРИГА	SRAM 90 Transmission
КУРБЕЛ	SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
СРЕДНА КАСЕТА	SRAM DUB, press fit

КАПЛИ	
ШИНИ	Giant XCA WheelSystem
ГЛАВИНИ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
СПИЦИ	Sapim
ГУМИ	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
ЕКСТРИ	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

## ГЕОМЕТРИЯ

РАМКА	S	M	L	XL
	LOW   HIGH	LOW   HIGH	LOW   HIGH	LOW   HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75,0°   75,5°	75,1°   75,5°	75,1°   75,6°	75,1°   75,6°
Top Tube Length (mm)	577   575	603   602	625   624	653   651
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,0°   66,5°	66,1°   66,5°	66,1°   66,6°	66,1°   66,6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	119,5   115,7	119,3   115,6	119,2   115,5	119   115,4
Wheelbase (mm)	1145   1144	1172   1171	1196   1195	1225   1224
Chain Stay Length (mm)	437   435	437   435	437   435	437   435
Bottom Bracket Drop (mm)	48   42	48   42	48   42	48   42
Stack (mm)	606   602	611   607	620   616	629   625
Обсер (mm)	415   420	440   445	460   465	485   490
Stand Over Height (mm)	774   780	770   776	762   769	757   764
Ширина на Кормило (mm)	780	780	780	780
Дължина на Лана (mm)	50	50	60	70
Дължина на Курбел (mm)	170	170	175	175

All specifications listed are subject to change without notice.