

ANTHEM X ADVANCED SL 2

GIANT



SPECIFIKATIONER

RAMME	
STØRRELSER	S, M, L, XL
FARVER	Dark Jungle
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORGAFFEL	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
BAGDÆMPER	Fox Float SL Performance, 210/50
KOMPONENTER	
STYR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GREB / STYRBÅND	Giant Tactal, lock on
FREMPIND	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SADELPIND	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SADEL	Giant Grit
PEDALER	N/A
GEARGRUPPE	
SKIFTEGREB	SRAM Eagle 90 mechanical, 1x12
FORSKIFTER	N/A
BAGSKIFTER	SRAM Eagle 90 Transmission
BREMSER	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSEGREB	Shimano SLX BL-M7100
KASSETTE	SRAM 70 1270, 10x52
KÆDE	SRAM 90 Transmission
KRANKSÆT	SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
KRANKBOKS	SRAM DUB, press fit

HJUL	
FÆLGE	Giant XCA WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EGER	Sapim
DÆK	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EKSTRA	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Pris: 43.499,00 kr.

GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Sadelrørlængde (mm)	400	420	465	495				
Sadelrørsvinkel	75,0°	75,5°	75,1°	75,5°	75,1°	75,6°	75,1°	75,6°
Overrørs længde (mm)	577	575	603	602	625	624	653	651
Kronrørlængde (mm)	90	95	105	115				
Kronrørsvinkel	66,0°	66,5°	66,1°	66,5°	66,1°	66,6°	66,1°	66,6°
Forgaffel fremspring (rake) (mm)	44	44	44	44				
Sti (mm)	119,5	115,7	119,3	115,6	119,2	115,5	119	115,4
Akselafstand (mm)	1145	1144	1172	1171	1196	1195	1225	1224
Kædestagslængde (mm)	437	435	437	435	437	435	437	435
Krankboks drop (mm)	48	42	48	42	48	42	48	42
Stack (mm)	606	602	611	607	620	616	629	625
Reach (mm)	415	420	440	445	460	465	485	490
Skridthøjde (mm)	774	780	770	776	762	769	757	764
Styrbredde (mm)	780	780	780	780				
Frempindslængde (mm)	50	50	60	70				
Pedalarmslængde (mm)	170	170	175	175				

Alle de anførte specifikationer kan ændres uden varsel.