

ANTHEM X ADVANCED SL 2



SPECS

FRAME	
SIZES	S, M, L, XL
COLOURS	Dark Jungle
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Performance
COMPONENTS	
HANDLEBAR	Giant Integrated XC, alloy, 9-degree upsweep
GRIPS	Giant Tactal, lock on
STEM	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 470mm XL: 140-170mm travel / 30.9 x 470mm
SADDLE	Giant Grit
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	SRAM Eagle 90, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	SRAM Eagle 90 T-Type
BRAKES	Shimano SLX BR-M7120 4 piston, hydraulic, Shimano RT-66 rotors [F]180mm, [R]160mm
BRAKE LEVERS	Shimano SLX BL-M7100
CASSETTE	SRAM XS-1270, T-Type 10x52
CHAIN	SRAM Eagle 70 T-Type
CRANKSET	SRAM Eagle 90 T-Type, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WHEELS	
RIMS	XCA 29 Alloy Wheelsystem
HUBS	[F] Giant alloy, 6-bolt [R] Giant Alloy, 120T Helical-Bevel Ratchet Driver, 6-Bolt
SPOKES	Sapim
TYRES	[F] Maxxis Rekon 29x2.4", TLR, EXO, tubeless, [R] Maxxis Rekon Race 29x2.4", TLR, EXO, tubeless
EXTRAS	Tubeless prepared, MRP 1x CS chain guide
LIMITS	
MAX TYRE CLEARANCE	2.4"
MAX CHAINRING SIZE	34t

Price: \$8,499.00

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	420	465	495				
Seat Tube Angle	75.0° 75.5°	75.1° 75.5°	75.1° 75.6°	75.1° 75.6°				
Top Tube Length (mm)	577 575	603 602	625 624	653 651				
Head Tube Length (mm)	90	95	105	115				
Head Tube Angle	66.0° 66.5°	66.1° 66.5°	66.1° 66.6°	66.1° 66.6°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	119.5 115.7	119.3 115.6	119.2 115.5	119 115.4				
Wheelbase (mm)	1145 1144	1172 1171	1196 1195	1225 1224				
Chain Stay Length (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	48 42	48 42	48 42	48 42				
Stack (mm)	606 602	611 607	620 616	629 625				
Reach (mm)	415 420	440 445	460 465	485 490				
Stand Over Height (mm)	774 780	770 776	762 769	757 764				
Stem Length (mm)	50	50	60	70				
Crank Length (mm)	170	170	175	175				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.