

ANTHEM X ADVANCED SL 2

GIANT



SPECS

| FRAME | |
|-------------------------|---|
| SIZES | S, M, L, XL |
| COLOURS | Dark Jungle |
| FRAME | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage |
| FORK | Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset |
| SHOCK | Fox Float SL Performance, 210/50 |
| COMPONENTS | |
| HANDLEBAR | Giant Integrated XC, alloy, 780mm, 9-degree upsweep |
| GRIPS | Giant Tactal, lock on |
| STEM | Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm |
| SEATPOST | Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 39.5mm M: 110-140mm travel / 30.9 x 39.5mm L: 140-170mm travel / 30.9 x 53.0mm |
| SADDLE | Giant Grit |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | SRAM Eagle 90 mechanical, 1x12 |
| FRONT DERAILLEUR | N/A |
| REAR DERAILLEUR | SRAM Eagle 90 Transmission |
| BRAKES | Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm |
| BRAKE LEVERS | Shimano SLX BL-M7100 |
| CASSETTE | SRAM 70 1270, 10x52 |
| CHAIN | SRAM 90 Transmission |
| CRANKSET | SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | SRAM DUB, press fit |

| WHEELS | |
|---------------|--|
| RIMS | Giant XCA WheelSystem |
| HUBS | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt |
| SPOKES | Sapim |
| TYRES | Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless |
| EXTRAS | tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide |

Price: £4,999.00

GEOMETRY

| FRAME | S | | M | | L | | XL | |
|--------------------------|---------------|-------|---------------|-------|---------------|-------|---------------|-------|
| | LOW | HIGH | LOW | HIGH | LOW | HIGH | LOW | HIGH |
| Seat Tube Length (mm) | 400 | | 420 | | 465 | | 495 | |
| Seat Tube Angle | 75.0° 75.5° | | 75.1° 75.5° | | 75.1° 75.6° | | 75.1° 75.6° | |
| Top Tube Length (mm) | 577 | 575 | 603 | 602 | 625 | 624 | 653 | 651 |
| Head Tube Length (mm) | 90 | | 95 | | 105 | | 115 | |
| Head Tube Angle | 66.0° 66.5° | | 66.1° 66.5° | | 66.1° 66.6° | | 66.1° 66.6° | |
| Fork Rake (mm) | 44 | | 44 | | 44 | | 44 | |
| Trail (mm) | 119.5 | 115.7 | 119.3 | 115.6 | 119.2 | 115.5 | 119 | 115.4 |
| Wheelbase (mm) | 1145 | 1144 | 1172 | 1171 | 1196 | 1195 | 1225 | 1224 |
| Chain Stay Length (mm) | 437 | 435 | 437 | 435 | 437 | 435 | 437 | 435 |
| Bottom Bracket Drop (mm) | 48 | 42 | 48 | 42 | 48 | 42 | 48 | 42 |
| Stack (mm) | 606 | 602 | 611 | 607 | 620 | 616 | 629 | 625 |
| Reach (mm) | 415 | 420 | 440 | 445 | 460 | 465 | 485 | 490 |
| Stand Over Height (mm) | 774 | 780 | 770 | 776 | 762 | 769 | 757 | 764 |
| Handlebar Width (mm) | 780 | | 780 | | 780 | | 780 | |
| Stem Length (mm) | 50 | | 50 | | 60 | | 70 | |
| Crank Length (mm) | 170 | | 170 | | 175 | | 175 | |

Every effort has been made to ensure accuracy throughout this website. However, Giant reserves the right to change bike specifications, features, prices and colours without prior notice.