

ANTHEM X ADVANCED SL 2

GIANT



SPECS

| FRAME | |
|-------------------------|---|
| SIZES | S, M, L, XL |
| COLORS | Dark Jungle |
| FRAME | Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage |
| FORK | Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset |
| SHOCK | Fox Float SL Performance, 210/50 |
| COMPONENTS | |
| HANDLEBAR | Giant Integrated XC, alloy, 780mm, 9-degree upsweep |
| GRIPS | Giant Tactal, lock on |
| STEM | Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm |
| SEATPOST | Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 39.5mm M: 110-140mm travel / 30.9 x 39.5mm L: 140-170mm travel / 30.9 x 53.0mm |
| SADDLE | Giant Grit |
| PEDALS | N/A |
| DRIVETRAIN | |
| SHIFTERS | SRAM Eagle 90 mechanical, 1x12 |
| FRONT DERAILLEUR | N/A |
| REAR DERAILLEUR | SRAM Eagle 90 Transmission |
| BRAKES | Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm |
| BRAKE LEVERS | Shimano SLX BL-M7100 |
| CASSETTE | SRAM 70 1270, 10x52 |
| CHAIN | SRAM 90 Transmission |
| CRANKSET | SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm |
| BOTTOM BRACKET | SRAM DUB, press fit |

| WHEELS | |
|---------------|--|
| RIMS | Giant XCA WheelSystem |
| HUBS | [F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt |
| SPOKES | Sapim |
| TIRES | Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless |
| EXTRAS | tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide |

Recommended Retail Price: \$5,600.00

GEOMETRY

| FRAME | S | | M | | L | | XL | |
|----------------------------|---------------|---------------|---------------|---------------|-----|------|-----|------|
| | LOW | HIGH | LOW | HIGH | LOW | HIGH | LOW | HIGH |
| Seat Tube Length (inch) | 15.7 | 16.5 | 18.3 | 19.5 | | | | |
| Seat Tube Angle | 75.0° 75.5° | 75.1° 75.5° | 75.1° 75.6° | 75.1° 75.6° | | | | |
| Top Tube Length (inch) | 22.7 22.6 | 23.7 23.7 | 24.6 24.6 | 25.7 25.6 | | | | |
| Head Tube Length (inch) | 3.5 | 3.7 | 4.1 | 4.5 | | | | |
| Head Tube Angle | 66.0° 66.5° | 66.1° 66.5° | 66.1° 66.6° | 66.1° 66.6° | | | | |
| Fork Rake (inch) | 1.7 | 1.7 | 1.7 | 1.7 | | | | |
| Trail (inch) | 4.7 4.5 | 4.7 4.5 | 4.7 4.5 | 4.7 4.5 | | | | |
| Wheelbase (inch) | 45.1 45 | 46.1 46.1 | 47.1 47 | 48.2 48.2 | | | | |
| Chain Stay Length (inch) | 17.2 17.1 | 17.2 17.1 | 17.2 17.1 | 17.2 17.1 | | | | |
| Bottom Bracket Drop (inch) | 1.9 1.7 | 1.9 1.7 | 1.9 1.7 | 1.9 1.7 | | | | |
| Stack (inch) | 23.9 23.7 | 24.1 23.9 | 24.4 24.3 | 24.8 24.6 | | | | |
| Reach (inch) | 16.3 16.5 | 17.3 17.5 | 18.1 18.3 | 19.1 19.3 | | | | |
| Stand Over Height (inch) | 30.5 30.7 | 30.3 30.6 | 30 30.3 | 29.8 30.1 | | | | |
| Handlebar Width (inch) | 30.7 | 30.7 | 30.7 | 30.7 | | | | |
| Stem Length (inch) | 2 | 2 | 2.4 | 2.8 | | | | |
| Crank Length (inch) | 6.7 | 6.7 | 6.9 | 6.9 | | | | |

**All specifications and prices listed are subject to change without notice. Actual weight may vary due to manufacturing tolerances, color variations, frame size and variability in production components.*