

ANTHEM X ADVANCED SL 2

GIANT



SPECIFICATIES

FRAME	
MATEN	S, M, L, XL
KLEUREN	Dark Jungle
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
VOORVORK	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
DEMPER	Fox Float SL Performance, 210/50
ONDERDELEN	
STUUR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
HANDVATTEN	Giant Tactal, lock on
STUURPEN	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
ZADELPEN	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
ZADEL	Giant Grit
PEDALEN	N/A
AFMONTAGE	
SHIFTERS	SRAM Eagle 90 mechanical, 1x12
VOORDERAILLEUR	N/A
ACHTERDERAILLEUR	SRAM Eagle 90 Transmission
REMMEN	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
REMHENDELS	Shimano SLX BL-M7100
CASSETTE	SRAM 70 1270, 10x52
AANDRIJVING	SRAM 90 Transmission
CRANKSET	SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

WIELSET	
VELGEN	Giant XCA WheelSystem
NAVEN	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPAKEN	Sapim
BANDEN	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRA'S	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Adviesprijs: € 5.499,00

GEOMETRIE

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Zitbuis lengte (mm)	400		420		465		495	
Zitbuis hoek	75,0°	75,5°	75,1°	75,5°	75,1°	75,6°	75,1°	75,6°
Frame Lengte (horizontaal) (mm)	577	575	603	602	625	624	653	651
Balhoofdbuis Lengte (mm)	90		95		105		115	
Balhoofdbuis Hoek	66,0°	66,5°	66,1°	66,5°	66,1°	66,6°	66,1°	66,6°
Vork Sprong (mm)	44		44		44		44	
Naloop (mm)	119,5	115,7	119,3	115,6	119,2	115,5	119	115,4
Wielbasis (mm)	1145	1144	1172	1171	1196	1195	1225	1224
Liggende achtervork lengte (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	48	42	48	42	48	42	48	42
Stack (mm)	606	602	611	607	620	616	629	625
Reach (mm)	415	420	440	445	460	465	485	490
Stand Over Height (mm)	774	780	770	776	762	769	757	764
Stuur breedte (mm)	780		780		780		780	
Stuurpen Lengte (mm)	50		50		60		70	
Cranklengte (mm)	170		170		175		175	

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.