

ANTHEM X ADVANCED SL 2

GIANT



SPECS

RAMME	
STØRRELSE	S, M, L, XL
FARGE	Dark Jungle
RAMME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
GAFFEL	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
DEMPER	Fox Float SL Performance, 210/50
KOMPONENTER	
STYRE	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
STYRSTEM	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SETEPINNE	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SADEL	Giant Grit
PEDALER	N/A
DRIVVERK	
GIRHENDLER	SRAM Eagle 90 mechanical, 1x12
FRONTGIR	N/A
BAKGIR	SRAM Eagle 90 Transmission
BREMSER	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSEHENDLER	Shimano SLX BL-M7100
KASSETT	SRAM 70 1270, 10x52
KJEDE	SRAM 90 Transmission
KRANK	SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

HJUL	
FELG	Giant XCA WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EIKE	Sapim
DEKK	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRI

RAMME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75,0°	75,5°	75,1°	75,5°	75,1°	75,6°	75,1°	75,6°
Top Tube Length (mm)	577	575	603	602	625	624	653	651
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66,0°	66,5°	66,1°	66,5°	66,1°	66,6°	66,1°	66,6°
Fork Rake (mm)	44		44		44		44	
Trail (mm)	119,5	115,7	119,3	115,6	119,2	115,5	119	115,4
Wheelbase (mm)	1145	1144	1172	1171	1196	1195	1225	1224
Chain Stay Length (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	48	42	48	42	48	42	48	42
Stack (mm)	606	602	611	607	620	616	629	625
Reach (mm)	415	420	440	445	460	465	485	490
Stand Over Height (mm)	774	780	770	776	762	769	757	764
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	50		50		60		70	
Crank Length (mm)	170		170		175		175	

Alle spesifikasjonene kan endres uten varsel.