

ANTHEM X ADVANCED SL 2

GIANT



SPECS

CADRU	
MARIMI	S, M, L, XL
CULORI	Dark Jungle
CADRU	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FURCA	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
SOC	Fox Float SL Performance, 210/50
COMPONENTE	
GHIDON	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
PIPA	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
TIJA SA	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SA	Giant Grit
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	SRAM Eagle 90 mechanical, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	SRAM Eagle 90 Transmission
FRANE	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
MANETE FRANA	Shimano SLX BL-M7100
PINIOANE	SRAM 70 1270, 10x52
LANT	SRAM 90 Transmission
ANGRENAJ	SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

ROTI	
JANTE	Giant XCA WheelSystem
BUTUCI	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPITE	Sapim
ANVELOPE	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIE

CADRU	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	420	465	495				
Seat Tube Angle	75,0° 75,5°	75,1° 75,5°	75,1° 75,6°	75,1° 75,6°	75,1° 75,6°			
Top Tube Length (mm)	577 575	603 602	625 624	653 651				
Head Tube Length (mm)	90	95	105	115				
Head Tube Angle	66,0° 66,5°	66,1° 66,5°	66,1° 66,6°	66,1° 66,6°	66,1° 66,6°			
Fork Rake (mm)	44	44	44	44				
Trail (mm)	119,5 115,7	119,3 115,6	119,2 115,5	119 115,4				
Wheelbase (mm)	1145 1144	1172 1171	1196 1195	1225 1224				
Chain Stay Length (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	48 42	48 42	48 42	48 42				
Stack (mm)	606 602	611 607	620 616	629 625				
Reach (mm)	415 420	440 445	460 465	485 490				
Stand Over Height (mm)	774 780	770 776	762 769	757 764				
Handlebar Width (mm)	780	780	780	780				
Stem Length (mm)	50	50	60	70				
Crank Length (mm)	170	170	175	175				

Toate specificatiile enumerate se pot schimba fara notificare prealabila.