



## SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Dark Jungle
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
VILICE	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
AMORTIZER	Fox Float SL Performance, 210/50
KOMPONENTE	
KRMILO	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
OPORA KRMILA	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
OPORA SEDEŽA	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SEDEŽ	Giant Grit
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	SRAM Eagle 90 mechanical, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	SRAM Eagle 90 Transmission
ZAVORE	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	Shimano SLX BL-M7100
VERIŽNIK	SRAM 70 1270, 10x52
VERIGA	SRAM 90 Transmission
GONILKE Z VERIŽNIKI	SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	SRAM DUB, press fit

OBROČNIKI	
OBROČI	Giant XCA WheelSystem
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
NAPERE	Sapim
PLAŠČI	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
DODATKI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

## GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400	420	465	495				
Kot sedežne cevi	75,0°	75,5°	75,1°	75,5°	75,1°	75,6°	75,1°	75,6°
Top Tube Length (mm)	577	575	603	602	625	624	653	651
Višina glave okvirja (mm)	90	95	105	115				
Krmilni kot	66,0°	66,5°	66,1°	66,5°	66,1°	66,6°	66,1°	66,6°
Zamik vpetja osi (mm)	44	44	44	44				
Trail (mm)	119,5	115,7	119,3	115,6	119,2	115,5	119	115,4
Medosna razdalja (mm)	1145	1144	1172	1171	1196	1195	1225	1224
Dolžina cevi ob verigi (mm)	437	435	437	435	437	435	437	435
Bottom Bracket Drop (mm)	48	42	48	42	48	42	48	42
Oddaljenost zgornje cevi od gonilne osi (mm)	606	602	611	607	620	616	629	625
Doseg (mm)	415	420	440	445	460	465	485	490
Višina zgornje cevi (mm)	774	780	770	776	762	769	757	764
Širina krmila (mm)	780	780	780	780				
Dolžina opore krmila (mm)	50	50	60	70				
Dolžina gonilke (mm)	170	170	175	175				

Vse navedene specifikacije se lahko spremenijo brez obvestila.