

# ANTHEM X ADVANCED SL 2

GIANT



## SPECS

RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Dark Jungle
RAM	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
GAFFEL	Fox 34 SL Performance, 130mm, GRIP damper, Boost 15x110, 44mm offset
BAKDÄMPARE	Fox Float SL Performance, 210/50
KOMPONENTER	
STYRE	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GREPPAR	Giant Tactal, lock on
STAM	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SADELSTOLPE	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SADEL	Giant Grit
PEDALER	N/A
DRIVLINJA	
VÄXLAR	SRAM Eagle 90 mechanical, 1x12
FRAMVÄXEL	N/A
BAKVÄXEL	SRAM Eagle 90 Transmission
BROMSAR	Shimano SLX BR-M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]180mm
BROMSSPAKAR	Shimano SLX BL-M7100
KASSETT	SRAM 70 1270, 10x52
KEDJA	SRAM 90 Transmission
VEVPARTI	SRAM 90 Transmission, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BROMSREGLAGE	SRAM DUB, press fit

HJUL	
FÄLGAR	Giant XCA WheelSystem
NAV	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
EKRAR	Sapim
DÄCK	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAFUNKTIONER	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

Price: 63 990,00 kr

## GEOMETRY

RAM	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Längd sadelrör (mm)	400		420		465		495	
Vinkel sadelrör	75,0°	75,5°	75,1°	75,5°	75,1°	75,6°	75,1°	75,6°
Topprörets längd (mm)	577	575	603	602	625	624	653	651
Styrhuvud Längd (mm)	90		95		105		115	
Vinkel styrhuvud	66,0°	66,5°	66,1°	66,5°	66,1°	66,6°	66,1°	66,6°
Gaffelvinkel (mm)	44		44		44		44	
Spår (mm)	119,5	115,7	119,3	115,6	119,2	115,5	119	115,4
Hjulbas (mm)	1145	1144	1172	1171	1196	1195	1225	1224
Kedjestagslängd (mm)	437	435	437	435	437	435	437	435
Nedre fäste Drop (mm)	48	42	48	42	48	42	48	42
Stack (mm)	606	602	611	607	620	616	629	625
Reach (mm)	415	420	440	445	460	465	485	490
Stå över höjden (mm)	774	780	770	776	762	769	757	764
Styrets bredd (mm)	780		780		780		780	
Stamlängd (mm)	50		50		60		70	
Vevlängd (mm)	170		170		175		175	

All specifications listed are subject to change without notice.