

ANTHEM X ADVANCED SL 3

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Carbon/Moon Dust
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Performance, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
STEM	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SEATPOST	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SADDLE	Giant Grit Core
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore mechanical, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore
BRAKES	TRP EVO Comp HD-M7040 hydraulic, stainless, 6-bolt rotors [F]203mm, [R]180mm
BRAKE LEVERS	TRP EVO Comp HD-M7040
CASSETTE	Shimano M6200, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant XCA WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75,0° 75,5°		75,1° 75,5°		75,1° 75,6°		75,1° 75,6°	
Top Tube Length (mm)	577 575		603 602		625 624		653 651	
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66,0° 66,5°		66,1° 66,5°		66,1° 66,6°		66,1° 66,6°	
Fork Rake (mm)	44		44		44		44	
Trail (mm)	119,5 115,7		119,3 115,6		119,2 115,5		119 115,4	
Wheelbase (mm)	1145 1144		1172 1171		1196 1195		1225 1224	
Chain Stay Length (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	48 42		48 42		48 42		48 42	
Stack (mm)	606 602		611 607		620 616		629 625	
Reach (mm)	415 420		440 445		460 465		485 490	
Stand Over Height (mm)	774 780		770 776		762 769		757 764	
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	50		50		60		70	
Crank Length (mm)	170		170		175		175	

All specifications listed are subject to change without notice.