ANTHEM X ADVANCED SL 3

SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Carbon/Moon Dust
RAHMEN	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
GABEL	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110, 44mm offset
DÄMPFER	Fox Float SL Performance, 210/50
KOMPONENTEN	
LENKER	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIFFE	Giant Tactal, lock on
VORBAU	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SATTEL	Giant Grit Core
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano Deore mechanical, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano Deore
BREMSEN	TRP EVO Comp HD-M7040 hydraulic, stainless, 6-bolt rotors [F]203mm, [R]180mm
BREMSHEBEL	TRP EVO Comp HD-M7040
KASSETTE	Shimano M6200, 10x51
KETTE	KMC X-12
KURBEL	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
TRETLAGER	Praxis, press fit

LAUFRÄDER	
FELGEN	Giant XCA WheelSystem
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPEICHEN	Sapim
REIFEN	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Sitzrohrlänge (mm)	400	420	465	495
Sitzrohrwinkel	75.0° | 75.5°	75.1° | 75.5°	75.1° | 75.6°	75.1° | 75.6°
Oberrohrlänge (mm)	577 | 575	603 | 602	625 | 624	653 | 651
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	66.0° | 66.5°	66.1° | 66.5°	66.1° | 66.6°	66.1° | 66.6°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	119.5 | 115.7	119.3 | 115.6	119.2 | 115.5	119 | 115.4
Radstand (mm)	1145 | 1144	1172 | 1171	1196 | 1195	1225 | 1224
Kettenstreben-Länge (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Tretlager-Höhe (mm)	48 | 42	48 | 42	48 | 42	48 | 42
Stack (mm)	606 | 602	611 | 607	620 | 616	629 | 625
Reach (mm)	415 | 420	440 | 445	460 | 465	485 | 490
Überstandshöhe (mm)	774 | 780	770 | 776	762 | 769	757 | 764
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	50	60	70
Kurbellänge (mm)	170	170	175	175

Spezifikations-, Preis- und Farbänderungen vorbehalten.