

# ANTHEM X ADVANCED SL 3

GIANT



## SPECS

ΣΚΕΛΕΤΟΣ	
ΜΕΓΕΘΗ	S, M, L, XL
ΧΡΩΜΑΤΑ	Carbon/Moon Dust
ΣΚΕΛΕΤΟΣ	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
ΠΙΡΟΥΝΙ	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110, 44mm offset
ΑΝΑΡΤΗΣΗ	Fox Float SL Performance, 210/50
ΕΞΑΡΤΗΜΑΤΑ	
ΤΙΜΟΝΙ	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
ΛΑΙΜΟΣ ΤΙΜΟΝΙΟΥ	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
ΛΑΙΜΟΣ ΣΕΛΛΑΣ	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
ΣΕΛΛΑ	Giant Grit Core
ΠΕΝΤΑΛ	N/A
ΜΕΤΑΔΟΣΗ	
ΛΕΒΙΕ ΤΑΧΥΤΗΤΩΝ	Shimano Deore mechanical, 1x12
ΝΤΕΡΑΓΙΕΡ ΕΜΠΡΟΣΘΙΟ	N/A
ΝΤΕΡΑΓΙΕΡ ΟΠΙΣΘΙΟ.	Shimano Deore
ΦΡΕΝΑ	TRP EVO Comp HD-M7040 hydraulic, stainless, 6-bolt rotors [F]203mm, [R]180mm
ΜΑΝ'ΕΤΤΕΣ ΦΡΕΝΩΝ	TRP EVO Comp HD-M7040
CASETTE Ή ΕΛΕΥΘΕΡΟ	Shimano M6200, 10x51
ΑΛΥΣΙΔΑ	KMC X-12
ΔΙΣΚΟΒΡΑΧΙΩΝΑΣ	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
ΒOTTOM BRACKET	Praxis, press fit

WHEELS	
ΣΤΕΦΑΝΙΑ	Giant XCA WheelSystem
ΚΕΝΤΡΑ	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
ΑΚΤΙΝΕΣ	Sapim
ΕΛΑΣΤΙΚΑ	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

## ΓΕΩΜΕΤΡΙΑ

ΣΚΕΛΕΤΟΣ	S	M	L	XL
	LOW   HIGH	LOW   HIGH	LOW   HIGH	LOW   HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75,0°   75,5°	75,1°   75,5°	75,1°   75,6°	75,1°   75,6°
Top Tube Length (mm)	577   575	603   602	625   624	653   651
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,0°   66,5°	66,1°   66,5°	66,1°   66,6°	66,1°   66,6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	119,5   115,7	119,3   115,6	119,2   115,5	119   115,4
Wheelbase (mm)	1145   1144	1172   1171	1196   1195	1225   1224
Chain Stay Length (mm)	437   435	437   435	437   435	437   435
Bottom Bracket Drop (mm)	48   42	48   42	48   42	48   42
Stack (mm)	606   602	611   607	620   616	629   625
Reach (mm)	415   420	440   445	460   465	485   490
Stand Over Height (mm)	774   780	770   776	762   769	757   764
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	50	50	60	70
Crank Length (mm)	170	170	175	175

Όλες οι προδιαγραφές είναι δυνατό να αλλάξουν χωρίς πρότερη ειδοποίηση