

ANTHEM X ADVANCED SL 3

GIANT



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Carbon/Moon Dust
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Performance
COMPONENTS	
HANDLEBAR	Giant Integrated XC, alloy, 9-degree upsweep
GRIPS	Giant Tactal Single lock-on
STEM	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SEATPOST	Giant Contact Switch AT dropper, adjustable travel, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9
SADDLE	Giant Grit Core
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore SL-M6100, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore SL-M6100 Shadow +
BRAKES	TRP Slate EVO hydraulic, stainless, 6-bolt rotors [F]203mm, [R]180mm
BRAKE LEVERS	TRP Slate EVO
CASSETTE	Shimano Deore M6100, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet HD M24, 32t, 55mm chainline S:165mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	XCA 29 Alloy Wheelssystem
HUBS	[F] Giant alloy, 6-bolt [R] Giant Alloy, 120T Helical-Bevel Ratchet Driver, 6-Bolt
SPOKES	Sapim
TIRES	[F] Maxxis Rekon 29x2.4", TLR, EXO, tubeless, [R] Maxxis Rekon Race 29x2.4", TLR, EXO, tubeless
EXTRAS	Tubeless prepared, 2.4" max tyre size, 34t max chainring size, MRP 1x CS chain guide

Price: \$8,499.00

GEOMETRY

FRAME	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400	420	465	495				
Seat Tube Angle	75.0° 75.5°	75.1° 75.5°	75.1° 75.6°	75.1° 75.6°				
Top Tube Length (mm)	577 575	603 602	625 624	653 651				
Head Tube Length (mm)	90	95	105	115				
Head Tube Angle	66.0° 66.5°	66.1° 66.5°	66.1° 66.6°	66.1° 66.6°				
Fork Rake (mm)	44	44	44	44				
Trail (mm)	119.5 115.7	119.3 115.6	119.2 115.5	119 115.4				
Wheelbase (mm)	1145 1144	1172 1171	1196 1195	1225 1224				
Chain Stay Length (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	48 42	48 42	48 42	48 42				
Stack (mm)	606 602	611 607	620 616	629 625				
Reach (mm)	415 420	440 445	460 465	485 490				
Stand Over Height (mm)	774 780	770 776	762 769	757 764				
Stem Length (mm)	50	50	60	70				
Crank Length (mm)	170	170	175	175				

Please note that our specifications may be impacted by running substitution changes, we highly recommend confirming the specifications of our products with your local retailer at the time of sale if purchasing in-store. *Recommended Retail Prices are subject to change without notice and may vary from store to store depending on freight and assembly costs.