ANTHEM X ADVANCED SL 3

SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Carbon/Moon Dust
FRAME	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FORK	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110, 44mm offset
SHOCK	Fox Float SL Performance, 210/50
COMPONENTS	
HANDLEBAR	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
STEM	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
SEATPOST	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SADDLE	Giant Grit Core
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Deore mechanical, 1x12
FRONT DERAILLEUR	N/A
REAR DERAILLEUR	Shimano Deore
BRAKES	TRP EVO Comp HD-M7040 hydraulic, stainless, 6-bolt rotors [F]203mm, [R]180mm
BRAKE LEVERS	TRP EVO Comp HD-M7040
CASSETTE	Shimano M6200, 10x51
CHAIN	KMC X-12
CRANKSET	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

WHEELS	
RIMS	Giant XCA WheelSystem
HUBS	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPOKES	Sapim
TIRES	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRY

FRAME	S	M	L	XL
	LOW | HIGH	LOW | HIGH	LOW | HIGH	LOW | HIGH
Seat Tube Length (mm)	400	420	465	495
Seat Tube Angle	75,0° | 75,5°	75,1° | 75,5°	75,1° | 75,6°	75,1° | 75,6°
Top Tube Length (mm)	577 | 575	603 | 602	625 | 624	653 | 651
Head Tube Length (mm)	90	95	105	115
Head Tube Angle	66,0° | 66,5°	66,1° | 66,5°	66,1° | 66,6°	66,1° | 66,6°
Fork Rake (mm)	44	44	44	44
Trail (mm)	119,5 | 115,7	119,3 | 115,6	119,2 | 115,5	119 | 115,4
Wheelbase (mm)	1145 | 1144	1172 | 1171	1196 | 1195	1225 | 1224
Chain Stay Length (mm)	437 | 435	437 | 435	437 | 435	437 | 435
Bottom Bracket Drop (mm)	48 | 42	48 | 42	48 | 42	48 | 42
Stack (mm)	606 | 602	611 | 607	620 | 616	629 | 625
Reach (mm)	415 | 420	440 | 445	460 | 465	485 | 490
Stand Over Height (mm)	774 | 780	770 | 776	762 | 769	757 | 764
Handlebar Width (mm)	780	780	780	780
Stem Length (mm)	50	50	60	70
Crank Length (mm)	170	170	175	175

All specifications listed are subject to change without notice.