

# ANTHEM X ADVANCED SL 3

**GIANT**



## SPECS

CADRU	
MARIMI	S, M, L, XL
CULORI	Carbon/Moon Dust
CADRU	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
FURCA	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110, 44mm offset
SOC	Fox Float SL Performance, 210/50
COMPONENTE	
GHIDON	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
PIPA	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
TIJA SA	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SA	Giant Grit Core
PEDALE	N/A
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano Deore mechanical, 1x12
SCHIMBATOR FATA	N/A
SCHIMBATOR SPATE	Shimano Deore
FRANE	TRP EVO Comp HD-M7040 hydraulic, stainless, 6-bolt rotors [F]203mm, [R]180mm
MANETE FRANA	TRP EVO Comp HD-M7040
PINIOANE	Shimano M6200, 10x51
LANT	KMC X-12
ANGRENAJ	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

ROTI	
JANTE	Giant XCA WheelSystem
BUTUCI	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
SPITE	Sapim
ANVELOPE	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

## GEOMETRIE

CADRU	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Seat Tube Length (mm)	400		420		465		495	
Seat Tube Angle	75,0°   75,5°		75,1°   75,5°		75,1°   75,6°		75,1°   75,6°	
Top Tube Length (mm)	577   575		603   602		625   624		653   651	
Head Tube Length (mm)	90		95		105		115	
Head Tube Angle	66,0°   66,5°		66,1°   66,5°		66,1°   66,6°		66,1°   66,6°	
Fork Rake (mm)	44		44		44		44	
Trail (mm)	119,5   115,7		119,3   115,6		119,2   115,5		119   115,4	
Wheelbase (mm)	1145   1144		1172   1171		1196   1195		1225   1224	
Chain Stay Length (mm)	437   435		437   435		437   435		437   435	
Bottom Bracket Drop (mm)	48   42		48   42		48   42		48   42	
Stack (mm)	606   602		611   607		620   616		629   625	
Reach (mm)	415   420		440   445		460   465		485   490	
Stand Over Height (mm)	774   780		770   776		762   769		757   764	
Handlebar Width (mm)	780		780		780		780	
Stem Length (mm)	50		50		60		70	
Crank Length (mm)	170		170		175		175	

Toate specificatiile enumerate se pot schimba fara notificare prealabila.