

ANTHEM X ADVANCED SL 3

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Carbon/Moon Dust
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
VILICE	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110, 44mm offset
AMORTIZER	Fox Float SL Performance, 210/50
KOMPONENTE	
KRMILO	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
GRIPS	Giant Tactal, lock on
OPORA KRMILA	Giant Integrated XC Alloy S:50mm, M:50mm, L:60mm, XL:70mm
OPORA SEDEŽA	Giant Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 110-140mm travel / 30.9 x 395mm L: 140-170mm travel / 30.9 x 530mm
SEDEŽ	Giant Grit Core
PEDALA	N/A
POGON	
PRESTAVNE ROČICE	Shimano Deore mechanical, 1x12
PREDNJI MENJALNIK	N/A
ZADNJI MENJALNIK	Shimano Deore
ZAVORE	TRP EVO Comp HD-M7040 hydraulic, stainless, 6-bolt rotors [F]203mm, [R]180mm
ZAVORNE ROČICE	TRP EVO Comp HD-M7040
VERIŽNIK	Shimano M6200, 10x51
VERIGA	KMC X-12
GONILKE Z VERIŽNIKI	Praxis Cadet HD M24, 32t, 55mm chainline S:170mm, M:170mm, L:175mm, XL:175mm
BOTTOM BRACKET	Praxis, press fit

OBROČNIKI	
OBROČI	Giant XCA WheelSystem
PESTA	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 6-bolt
NAPERE	Sapim
PLAŠČI	Maxxis Rekon Race 29x2.4, foldable, 120tpi, EXO, tubeless
DODATKI	tubeless prepared, 2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400	420	465	495				
Kot sedežne cevi	75,0° 75,5°	75,1° 75,5°	75,1° 75,6°	75,1° 75,6°				
Top Tube Length (mm)	577 575	603 602	625 624	653 651				
Višina glave okvirja (mm)	90	95	105	115				
Krmlni kot	66,0° 66,5°	66,1° 66,5°	66,1° 66,6°	66,1° 66,6°				
Zamik vpetja osi (mm)	44	44	44	44				
Trail (mm)	119,5 115,7	119,3 115,6	119,2 115,5	119 115,4				
Medosna razdalja (mm)	1145 1144	1172 1171	1196 1195	1225 1224				
Dolžina cevi ob verigi (mm)	437 435	437 435	437 435	437 435				
Bottom Bracket Drop (mm)	48 42	48 42	48 42	48 42				
Oddaljenost zgornje cevi od gonilne osi (mm)	606 602	611 607	620 616	629 625				
Doseg (mm)	415 420	440 445	460 465	485 490				
Višina zgornje cevi (mm)	774 780	770 776	762 769	757 764				
Širina krmila (mm)	780	780	780	780				
Dolžina opore krmila (mm)	50	50	60	70				
Dolžina gonilke (mm)	170	170	175	175				

Vse navedene specifikacije se lahko spremenijo brez obvestila.