

ANTHEM X ADVANCED SL 3



SPECIFIKACIJE

OKVIR	
OKVIR	Advanced SL-Grade Composite Front and Rear triangles Flexpoint Pro Suspension / Internal Frame Storage Suspension Travel: 120mm Rear, 130mm Front Frame size S, M, L, XL 29" Wheels front and rear
VILICE	Fox 34 Rhythm Grip
AMORTIZER	Fox Float SL Performance
KOMPONENTE	
KRMILO	Giant Integrated 1pcs Alloy Bar/Stem w/ Internal Routing
GRIPS	Giant Tactal lock on
OPORA SEDEŽA	Giant OBC Contact Switch AT
SEDEŽ	Giant Grit Core
HEADSET	Integrated Internal cable Routing ZS56 Interface Upper & Lower
POGON	
PRESTAVNE ROČICE	Shimano Deore 1x12 SL-M6200-R
ZADNJI MENJALNIK	Shimano Deore RD-M7200 1x12 Shadow ES
ZAVORE	TRP EVO Comp HD-M7040 4 piston
ZAVORNE ROČICE	TRP EVO Comp HD-M7040 Slate EVO
VERIŽNIK	Shimano Deore CS-M6200-12 10x51, 12-speed
VERIGA	KMC X12
GONILKE Z VERIŽNIKI	Praxis Cadet HD M24 32T
BOTTOM BRACKET	Praxis PressFit

OBROČNIKI	
OBROČI	New XCA 29 Alloy Wheelsystem
PESTA	New XCA 29 Alloy Wheelsystem
NAPERE	Sapim
PLAŠČI	Maxxis 29x2.4" Rekon (Front) Rekon Race (Rear)
DODATKI	MRP 1x CS (Global) Chainguide MRP 1x CS HD2 (GA) Chainguide Giant Branded Internal Frame Storage Bag

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW HIGH		LOW HIGH		LOW HIGH		LOW HIGH	
Kot sedežne cevi	75,5° 76,0°		75,5° 76,0°		75,5° 76,0°		75,5° 76,0°	
Top Tube Length (mm)	576 574		602 600		624 623		651 650	
Višina glave okvirja (mm)	90		95		105		115	
Krnilni kot	66,5° 67,0°		66,5° 67,0°		66,5° 67,0°		66,5° 67,0°	
Medosna razdalja (mm)	1141 1140		1168 1167		1192 1191		1221 1220	
Dolžina cevi ob verigi (mm)	437 435		437 435		437 435		437 435	
Oddaljenost zgornje cevi od gonilne osi (mm)	602 599		607 603		616 612		626 622	
Doseg (mm)	420 425		445 450		465 470		490 495	
Višina zgornje cevi (mm)	769 775		764 771		758 763		751 758	
Dolžina gonilke (mm)	170		170		175		175	

Vse navedene specifikacije se lahko spremenijo brez obvestila.