

ANTHEM X ADVANCED SL FRAME

GIANT



SPECIFIKACIJE

OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Pixel Pulse
OKVIR	Advanced SL-grade composite front and rear triangles, 120mm FlexPoint Pro suspension, flip chip, 12x148mm thru-axle, internal storage
VILICE	N/A
AMORTIZER	Fox Float SL Factory, 210/50
KOMPONENTE	
KRMILO	Giant Integrated XC, alloy, 780mm, 9-degree upsweep
OPORA KRMILA	Giant Integrated XC, alloy S:50mm, M:50mm, L:60mm, XL:70mm
OPORA SEDEŽA	N/A

OBROČNIKI	
DODATKI	2.4" max tire size, 34t max chainring size, MRP 1x CS chain guide

GEOMETRIJA

OKVIR	S		M		L		XL	
	LOW	HIGH	LOW	HIGH	LOW	HIGH	LOW	HIGH
Dolžina sedežne cevi (mm)	400		420		465		495	
Kot sedežne cevi	75,0° 75,5°		75,1° 75,5°		75,1° 75,6°		75,1° 75,6°	
Top Tube Length (mm)	577 575		603 602		625 624		653 651	
Višina glave okvirja (mm)	90		95		105		115	
Krmilni kot	66,0° 66,5°		66,1° 66,5°		66,1° 66,6°		66,1° 66,6°	
Zamik vpetja osi (mm)	44		44		44		44	
Trail (mm)	119,5 115,7		119,3 115,6		119,2 115,5		119 115,4	
Medosna razdalja (mm)	1145 1144		1172 1171		1196 1195		1225 1224	
Dolžina cevi ob verigi (mm)	437 435		437 435		437 435		437 435	
Bottom Bracket Drop (mm)	48 42		48 42		48 42		48 42	
Oddaljenost zgornje cevi od gonilne osi (mm)	606 602		611 607		620 616		629 625	
Doseg (mm)	415 420		440 445		460 465		485 490	
Višina zgornje cevi (mm)	774 780		770 776		762 769		757 764	
Širina krmila (mm)	780		780		780		780	
Dolžina opore krmila (mm)	50		50		60		70	
Dolžina gonilke (mm)	170		170		175		175	

Vse navedene specifikacije se lahko spremenijo brez obvestila.