

ANYTOUR E+ 0

GIANT



SPECIFICATIES

| HYBRID CYCLING TECHNOLOGY | |
|---------------------------|---|
| MOTOR | Giant SyncDrive Sport2 75Nm, powered by Yamaha, PedalPlus 6-Sensor technology |
| BEDIENINGSUNIT | Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W) |
| DISPLAY | Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation |
| ACCU | Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production |
| LADER | Giant EnergyPak 6A smart charger, 60% charge in 3:00h |
| CONNECTIVITY | Giant RideControl App enabled ANT+ wireless display signal with e-bike profile |
| FRAME | |
| MATEN | S, M, L, XL |
| KLEUREN | Space Grey / Black |
| FRAME | ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand |
| VOORVORK | SR Suntour MOBIE 25 LOR 700C Air 63mm travel, 15x100mm 15AH2 thru-axle |
| DEMPER | n/a |
| ONDERDELEN | |
| STUUR | Giant Contour GT, cable integrated, 30° back sweep, 31.8x660mm |
| HANDVATTEN | Connect Ergo Max Sweep |
| STUURPEN | Giant Contour, EVO display integrated, adjustable |
| ZADEL | Suspension dropper post, handlebar operated remote control, 30.9mm |
| ZADEL | Selle Royal Look-In gel |
| PEDALEN | VP-831P |
| AFMONTAGE | |
| SHIFTERS | Enviolo Automatiq Pure (AHI-PURE-44T-OE) |
| VOORDERAILLEUR | n/a |
| ACHTERDERAILLEUR | n/a |
| REMMEN | Magura MT5, hydraulic disc, 180mm |
| REMHENDELS | Magura MT5 |
| CASSETTE | Gates CDXtm stainless steel 22T rear sprocket |
| AANDRIJVING | Gates CDXtm Carbon Drive 120T CenterTrack belt |
| CRANKSET | Gates CDXtm CenterTrack 46T front sprocket |
| BOTTOM BRACKET | n/a |

| WIELSET | |
|--------------------|---|
| VELGEN | Giant eX 2, Tubeless Ready, 700c Aluminium |
| NAVEN | Giant eTracker 100x15mm thru-axle 6 bolts disc [F] Enviolo Trekking AUTOMATIQ [R] |
| SPAKEN | Stainless |
| BANDEN | Schwalbe Marathon E Plus 622x50, Smart DualGuard Addix E |
| EXTRA'S | KSA40 direct mount kickstand |
| ACCESSOIRES | |
| VERLICHTING | Giant Recon HL100, 100 lux [F] AXA Juno 6-12V E-bike tail light with brake sensor [R] |
| SLOT | ABUS Xplus Battery Lock / Abus S755L XPlus R (ART certified) |
| DRAGER | MIK HD rack. System bag & basket compatible |

Adviesprijs: € 5.599,00

GEOMETRIE

| FRAME | S | M | L | XL |
|---------------------------------|-------|-------|-------|-------|
| Zitbuis Lengte (mm) | 410 | 460 | 480 | 550 |
| Zitbuis Hoek | 72,5° | 72,5° | 72,0° | 72,0° |
| Frame Lengte (horizontaal) (mm) | 590 | 590 | 610 | 630 |
| Balhoofdbuis Lengte (mm) | 130 | 130 | 170 | 170 |
| Balhoofdbuis Hoek | 69,5° | 69,5° | 69,5° | 69,5° |
| Vork Sprong (mm) | 44 | 44 | 44 | 44 |
| Naloop (mm) | 90,6 | 91 | 91 | 91 |
| Wielbasis (mm) | 1114 | 1114 | 1130 | 1150 |
| Liggende achtervork lengte (mm) | 470 | 470 | 470 | 470 |
| Bottom Bracket Drop (mm) | 70 | 70 | 70 | 70 |
| Stack (mm) | 663 | 663 | 663 | 663 |
| Reach (mm) | 392 | 392 | 394 | 414 |
| Stand Over Height (mm) | 588 | 588 | 540 | 527 |
| Stuur breedte (mm) | 660 | 660 | 660 | 660 |
| Stuurpen Lengte (mm) | 90 | 90 | 110 | 110 |
| Cranklengte (mm) | 170 | 170 | 170 | 170 |
| Wielmaat | 700C | 700C | 700C | 700C |

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.