

ANYTOUR E+ 0 LST



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
TIPALO	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
TIPALA	Aegis Radarand Aegis Tire Checker (TPMS)
PRIKAZOVALNIK	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIJA	Giant EnergyPak 800Wh
CHARGER	Giant EnergyPak 4A smart charger
OKVIR	
VELIKOSTI	S, M, L, XL
OKVIR	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand
VILICE	SR Suntour MOBIE 34 2CR Air 60mm travel 15x100mm thru-axle
KOMPONENTE	
KRMILO	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
OPORA KRMILA	Giant Contour, EVO display integrated, adjustable
OPORA SEDEŽA	Suspension dropper post, 30.9mm
SEDEŽ	Selle Royal Look-In gel Moderate Wide
PEDALA	Anti-slip Platform
POGON	
PRESTAVNE ROČICE	Giant RideControl Ergo4 Remote (E-Shift integrated)
ZAVORE	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 203mm [F] 180mm [R]
ZAVORNE ROČICE	Shimano Deore, BL-M401
VERIŽNIK	Gates CDX stainless steel 22T rear sprocket
VERIGA	Gates CDX Carbon Drive 120T CenterTrack belt
GONILKE Z VERIŽNIKI	Forged aluminum crank arms

OBROČNIKI	
OBROČI	Giant eX 2 700c Tubeless Ready Aluminium 622x21
PESTA	Giant 15X100mm [F] Enviolo Trekking V3 Automatic [R]
NAPERE	Stainless
PLAŠČI	Schwalbe Marathon E Plus, 622x50, Smart DualGuard Addix E
DODATKI	KSA40 direct mount kickstand
DODATNA OPREMA	
SVETILA	Supernova mini 2 LDM [F] Aegis carrier integrated tail light [R]
KLJUČAVNICA	Abus Xplus Battery Lock / Abus 6950L XPlus NR
PRTLJAŽNIK	MIK HD rack. System bag, basket and Aegis radar compatible
BLATNIKI/ŠČITNIK VERIGE	Aluminium Fender w/ Z-Reflector / Pistol shape chainguard
LIMITS	
MAX CHAINRING SIZE	Gates CDX CenterTrack 46T front sprocket

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	380	450	480	550
Kot sedežne cevi	73,5°	72,5°	72,0°	72,0°
Top Tube Length (mm)	570	590	610	630
Višina glave okvirja (mm)	130	170	170	170
Krmlilni kot	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	90,6	90,6	90,6	90,6
Medosna razdalja (mm)	1106,3	1116,5	1130,1	1150,1
Dolžina cevi ob verigi (mm)	472	472	472	472
Bottom Bracket Drop (mm)	70	70	70	70
Oddaljenost zgornje cevi od gonilne osi (mm)	625,9	663,3	663,3	663,3
Doseg (mm)	384,3	380,5	394,1	414,1
Širina krmila (mm)	660	660	660	660
Dolžina opore krmila (mm)	90	90	110	110
Dolžina gonilke (mm)	170	170	170	170
Velikost obročnikov	622X50	622X50	622X50	622X50

Vse navedene specifikacije se lahko spremenijo brez obvestila.