

ANYTOUR E+ 0 LST



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
KONTROLLER	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
SENSORER	Aegis Radarand Aegis Tire Checker (TPMS)
VISA	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERI	Personal battery choice 500 Wh, 625 Wh or 800 Wh (suggested retail price based on 500 Wh)
LADDARE	Giant EnergyPak 4A smart charger
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Metal
RAM	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand
GAFFEL	SR Suntour MOBIE 34 2CR Air 60mm travel 15x100mm thru-axle
KOMPONENTER	
STYRE	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660mm
GREPPAR	Giant Comfort Ergo Microtech Plus Lock-on
STAM	Giant Contour, EVO display integrated, adjustable
SADELSTOLPE	Suspension dropper post, 30.9mm
SADEL	Selle Royal Look-In gel Moderate Wide
PEDALER	Anti-slip Platform
DRIVLINA	
VÄXLAR	Giant RideControl Ergo4 Remote (E-Shift integrated)
BROMSAR	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 203mm [F] 180mm [R]
BROMSSPAKAR	Shimano Deore, BL-M401
KASSETT	Gates CDX stainless steel 22T rear sprocket
KEDJA	Gates CDX Carbon Drive 120T CenterTrack belt
VEVPARTI	Forged alumium crank arms

HJUL	
FÄLGAR	Giant eX 2 700c Tubeless Ready Aluminium 622x21
NAV	Giant 15X100mm [F] Enviolo Trekking V3 Automatic [R]
EKRAR	Stainless
DÄCK	Schwalbe Marathon E Plus, 622x50, Smart DualGuard Addix E
EXTRAFUNKTIONER	KSA40 direct mount kickstand
TILLBEHÖR	
BELYSNING	Supernova mini 2 LDM [F] Aegis carrier integrated tail light [R]
LÅSA	Abus Xplus Battery Lock / Abus 6950L XPlus NR
BÄRARE	MIK HD rack. System bag, basket and Aegis radar compatible
STÄNKSKÄRM/KEDJESKYDD	Aluminium Fender w/ Z-Reflector / Pistol shape chainguard
GRÄNSER	
MAX KEDJERINGSTORLEK	Gates CDX CenterTrack 46T front sprocket

Price: 64 990,00 kr

GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	380	450	480	550
Vinkel sadelrör	73,5°	72,5°	72,0°	72,0°
Topprörets längd (mm)	570	590	610	630
Styrhuvud Längd (mm)	130	170	170	170
Vinkel styrhuvud	69,5°	69,5°	69,5°	69,5°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	90,6	90,6	90,6	90,6
Hjulbas (mm)	1106,3	1116,5	1130,1	1150,1
Kedjestagslängd (mm)	472	472	472	472
Nedre fäste Drop (mm)	70	70	70	70
Stack (mm)	625,9	663,3	663,3	663,3
Reach (mm)	384,3	380,5	394,1	414,1
Styrets bredd (mm)	660	660	660	660
Stamlängd (mm)	90	90	110	110
Vevlängd (mm)	170	170	170	170
Hjulstorlek	622X50	622X50	622X50	622X50

All specifications listed are subject to change without notice.