

ANYTOUR E+ 1 GB



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Sport2 75Nm, powered by Yamaha, PedalPlus 6-Sensor technology
KONTROLLER	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
VISA	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERI	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
LADDARE	Giant EnergyPak 6A smart charger, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Black Diamond, Amber Glow
RAM	New ALUXX aluminum for Sport2 motor with integrated cable routing
GAFFEL	SR Suntour NCX32 E LO 29" Air 63mm travel
BAKDÄMPARE	n/a
KOMPONENTER	
STYRE	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660mm
GREPPAR	Giant Comfort Ergo Microtech Plus Lock-on
STAM	Giant Contour, EVO display integrated, adjustable
SADELSTOLPE	Suspension seat post, 30.9mm
SADEL	Selle Royal Look-In gel
PEDALER	VP-831P
DRIVLINJA	
VÄXLAR	Shimano E5, 5-speed Revoshift
FRAMVÄXEL	n/a
BAKVÄXEL	n/a
BROMSAR	Shimano Deore, BR-MT410, hydraulic disc, 180mm
BROMSSPAKAR	Shimano Deore, BL-MT401
KASSETT	Gates CDXtm stainless steel 32T rear sprocket
KEDJA	Gates CDXtm Carbon Drive 125T CenterTrack belt
VEVPARTI	Gates CDXtm CenterTrack 46T front sprocket
BROMSREGLAGE	n/a

HJUL	
FÄLGAR	Giant eX 2, Tubeless Ready, 700c Aluminium
NAV	Shimano HB-TC500-15, 100x15mm thru-axle Disc [F] Shimano Nexus E5 Disc brake [R]
EKRAR	Stainless
DÄCK	Schwalbe Marathon E Plus 622x50, Smart DualGuard Addix E
EXTRAFUNKTIONER	KSA40 direct mount kickstand
TILLBEHÖR	
BELYSNING	Giant Recon HL50, 50 lux [F] AXA Juno 6-12V E-bike tail light [R]
LÅSA	ABUS Xplus Battery Lock / Abus 5755L XPUS NR
BÄRARE	MIK HD rack. System bag & basket compatible

Price: 54 190,00 kr

GEOMETRY

RAM	S	M
Längd sadelrör (mm)	410	460
Vinkel sadelrör	72,5°	72,5°
Topprörets längd (mm)	590	590
Styrhuvud Längd (mm)	130	130
Vinkel styrhuvud	69,5°	69,5°
Gaffelvinkel (mm)	44	44
Spår (mm)	90,6	91
Hjulbas (mm)	1114	1114
Kedjestagslängd (mm)	470	470
Nedre fäste Drop (mm)	70	70
Stack (mm)	663	663
Reach (mm)	392	392
Stå över höjden (mm)	588	588
Styrets bredd (mm)	660	660
Stamlängd (mm)	90	90
Vevlängd (mm)	170	170
Hjulstorlek	700C	700C

All specifications listed are subject to change without notice.