

ANYTOUR E+ 1 LST

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
CONTROLLER	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
SENSORS	Aegis Radar and Aegis Tire Checker
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERY	Giant EnergyPak 800Wh
CHARGER	Giant EnergyPak 4A smart charger
FRAME	
SIZES	S, M, L, XL
FRAME	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand
FORK	SR Suntour MOBIE 34 2CR Air 60mm travel 15x100mm thru-axle
COMPONENTS	
HANDLEBAR	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
STEM	Giant Contour, EVO display integrated, adjustable
SEATPOST	Suspension dropper post, 30.9mm
SADDLE	Selle Royal Look-In gel Moderate Wide
PEDALS	Anti-slip Platform
DRIVETRAIN	
SHIFTERS	Giant RideControl Ergo4 Remote (E-Shift integrated)
REAR DERAILLEUR	Shimano Cues LinkGlide Di2, 11-Speed
BRAKES	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 180mm [F/R]
BRAKE LEVERS	Shimano Deore, BL-M401
CASSETTE	Shimano Cues LinkGlide, 11-speed, 11-45T
CHAIN	Shimano LinkGlide
CRANKSET	Forged alumium crank arms

WHEELS	
RIMS	Giant eX 2 700c Tubeless Ready Aluminium 622x21
HUBS	Shimano 15x100mm [F] Shimano FH-QC400-HM [R]
SPOKES	Stainless
TYRES	Schwalbe Marathon E Plus, 622x50, Smart DualGuard Addix E
EXTRAS	KSA40 direct mount kickstand,
ACCESSORIES	
LIGHTING	Supernova mini 2 LDM [F] Aegis carrier integrated tail light [R]
LOCK	Abus Xplus Battery Lock / Abus 6950L XPlus NR
CARRIER	MIK HD rack. System bag, basket and Aegis radar compatible
FENDER/CHAINGUARD	Pistol shape, Aluminium Fender w/ Z-Reflector
LIMITS	
MAX CHAINRING SIZE	42T

Price: €5,275.00

GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	380	450	480
Seat Tube Angle	73.5°	72.5°	72.0°
Top Tube Length (mm)	570	590	610
Head Tube Length (mm)	130	170	170
Head Tube Angle	69.5°	69.5°	69.5°
Fork Rake (mm)	44	44	44
Trail (mm)	90.6	90.6	90.6
Wheelbase (mm)	1106.3	1116.5	1130.1
Chain Stay Length (mm)	472	472	472
Bottom Bracket Drop (mm)	70	70	70
Stack (mm)	625.9	663.3	663.3
Reach (mm)	384.3	380.5	394.1
Handlebar Width (mm)	660	660	660
Stem Length (mm)	90	90	110
Crank Length (mm)	170	170	170
Wheel Size	622X50	622X50	622X50

All specifications listed are subject to change without notice.