

ANYTOUR E+ 1 LST



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
OHJAUSYKSIKKÖ	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
SENSORIT	Aegis Radar and Aegis Tire Checker
NÄYTTÖ	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
AKKU	Personal battery choice 500 Wh, 625 Wh or 800 Wh (suggested retail price based on 500 Wh)
LATURI	Giant EnergyPak 4A smart charger
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Panther
RUNKO	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand
HAARUKKA	SR Suntour MOBIE 34 2CR Air 60mm travel 15x100mm thru-axle
KOMONENTIT	
OHJAUSTANKO	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660mm
GRIPIT	Giant Comfort Ergo Microtech Plus Lock-on
OHJAINKANNATIN	Giant Contour, EVO display integrated, adjustable
SATULATOLPPA	Suspension dropper post, 30.9mm
SATULA	Selle Royal Look-In gel Moderate Wide
POLKIMET	Anti-slip Platform
VOIMANSIIRTO	
VAIHDEVIPU	Giant RideControl Ergo4 Remote (E-Shift integrated)
TAKAVAIHTAJA	Shimano Cues LinkGlide Di2, 11-Speed
JARRUT	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 180mm [F/R]
JARRUKAHVAT	Shimano Deore, BL-M401
RATASPAKKA	Shimano Cues LinkGlide, 11-speed, 11-45T
KETJUT	Shimano LinkGlide
KAMPISARJA	Forged alumium crank arms

RENKAAT	
VANTEET	Giant eX 2 700c Tubeless Ready Aluminium 622x21
NAVAT	Shimano 15x100mm [F] Shimano FH-QC400-HM [R]
PINNAT	Stainless
RENKAAT	Schwalbe Marathon E Plus, 622x50, Smart DualGuard Addix E
LISÄTIEDOT	KSA40 direct mount kickstand,
TARVIKKEET	
VALOT	Supernova mini 2 LDM [F] Aegis carrier integrated tail light [R]
LUKKO	Abus Xplus Battery Lock / Abus 6950L XPlus NR
TAVARATELINE	MIK HD rack. System bag, basket and Aegis radar compatible
KETJUNSUOJA	Pistol shape, Aluminium Fender w/ Z-Reflector
RAJOITTEET	
MAX KETJUN KOKO	42T

Suositusinta: 4 799,00 €

GEOMETRIA

RUNKO	S	M	L	XL
Satulaputken pituus (mm)	380	450	480	550
Satulaputken kulma	73,5°	72,5°	72,0°	72,0°
Vaakaputken pituus (mm)	570	590	610	630
Emäputken pituus (mm)	130	170	170	170
Emäputken kulma	69,5°	69,5°	69,5°	69,5°
Haarukan offset (mm)	44	44	44	44
Trail-mitta (mm)	90,6	90,6	90,6	90,6
Akseliväli (mm)	1106,3	1116,5	1130,1	1150,1
Takahaarukan alaputken pituus (mm)	472	472	472	472
Keskiön pudotus (mm)	70	70	70	70
Stack-mitta (mm)	625,9	663,3	663,3	663,3
Reach-mitta (mm)	384,3	380,5	394,1	414,1
Ohjaustangon leveys (mm)	660	660	660	660
Ohjainkannattimen pituus (mm)	90	90	110	110
Kammen pituus (mm)	170	170	170	170
Rengaskoko	622X50	622X50	622X50	622X50

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.