

ANYTOUR E+ 3 LST



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2 75Nm, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Single sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	Personal battery choice 500 Wh, 625 Wh or 800 Wh (suggested retail price based on 500 Wh)
LADER	Giant EnergyPak 4A smart charger
FRAME	
MATEN	S, M, L, XL
KLEUREN	Stealth Chrome, Mountain Air
FRAME	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand
VOORVORK	SR Suntour MOBIE 34 2CR Air 60mm travel 15x100mm thru-axle
ONDERDELEN	
STUUR	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660mm
HANDVATTEN	Giant Comfort Ergo Microtech Plus Lock-on
STUURPEN	Giant Contour, EVO display integrated, adjustable
ZADEL PEN	Suspension dropper post, 30.9mm
ZADEL	Selle Royal Look-In gel Moderate Wide
PEDALEN	Anti-slip Platform
AFMONTAGE	
SHIFTERS	Shimano Nexus 8-speed RevoShift
REMMEN	Shimano MT-200, hydraulic disc, 180mm [F/R]
REMHENDELS	Shimano MT-200
CASSETTE	Gates CDC stainless steel 22T rear sprocket
AANDRIJVING	Gates CDC Carbon Drive 120T CenterTrack belt
CRANKSET	Gates CDC CenterTrack 46T front sprocket, Forged alumium crank arms

WIELSET	
VELGEN	Giant eX 2 700c Tubeless Ready Aluminium 622x21
NAVEN	Shimano 15x100mm [F] Shimano Nexus 8 disc brake [R]
SPAKEN	Stainless
BANDEN	Schwalbe Marathon E Plus, 622x50, Smart DualGuard Addix E
EXTRA'S	KSA40 direct mount kickstand
ACCESSOIRES	
VERLICHTING	Giant Recon HL50, 50 lux [F] Aegis carrier integrated tail light [R]
SLOT	Abus Xplus Battery Lock / Abus 6950L XPlus NR
DRAGER	MIK HD rack. System bag, basket and Aegis radar compatible
SPATBORD/ KETTINGKAST	Aluminium Fender w/ Z-Reflector, Pistol shape

Adviesprijs: € 3.799,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	380	450	480	550
Zitbuis Hoek	73,5°	72,5°	72,0°	72,0°
Frame Lengte (horizontaal) (mm)	570	590	610	630
Balhoofdbuis Lengte (mm)	130	170	170	170
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	90,6	90,6	90,6	90,6
Wielbasis (mm)	1106,3	1116,5	1130,1	1150,1
Liggende achtervork lengte (mm)	472	472	472	472
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	625,9	663,3	663,3	663,3
Reach (mm)	384,3	380,5	394,1	414,1
Stuur breedte (mm)	660	660	660	660
Stuurpen Lengte (mm)	90	90	110	110
Cranklengte (mm)	170	170	170	170
Wielmaat	622X50	622X50	622X50	622X50

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.