

ANYTOUR E+ 3 LST

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY

MOTOR	Giant SyncDrive Core, 55Nm, Powered by Yamaha, PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production

FRAME

MATEN	S, M, L, XL
KLEUREN	Eclipse / Black, Sandshell / Black, Mineral Yellow
FRAME	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand
VOORVORK	SR Suntour NEX E25 NLO 700C Coil 63mm, 15x100mm thru-axle
DEMPER	n/a

ONDERDELEN

STUUR	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm
HANDVATTEN	Giant Comfort Ergo Microtech Plus Lock-on
STUURPEN	Giant Contour, EVO display integrated, adjustable
ZADEL	Selle Royal Look-In gel
PEDALEN	Aluminum, Wellgo C211DU

AFMONTAGE

SHIFTERS	Shimano Nexus 8speed Revoshift
REMMEN	Shimano BR-MT200, hydraulic disc, 180mm
REMHENDELS	Shimano BL-MT200
CASSETTE	Gates CDC stainless steel 22T rear sprocket
AANDRIJVING	Gates CDC Carbon Drive 120T CenterTrack belt
CRANKSET	Gates CDC CenterTrack 46T front sprocket
BOTTOM BRACKET	n/a

WIELSET

VELGEN	Giant eX 2, Tubeless Ready, 700c Aluminium
NAVEN	Shimano HB-TC500-15, 100x15mm thru-axle Disc [F], Shimano Nexus 8 Disc brake [R]
SPAKEN	Stainless
BANDEN	Schwalbe Marathon E Plus 622x50, Smart DualGuard Addix E
ACCESSOIRES	
VERLICHTING	Giant Recon HL50, 50 lux [F] AXA Juno 6-12V E-bike tail light [R]
SLOT	ABUS Xplus Battery Lock / Abus S755L XPlus R (ART certified)
DRAGER	MIK HD rack. System bag & basket compatible

Adviesprijs: € 3.799,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	410	460	480	550
Zitbuis Hoek	72,5°	72,5°	72,0°	72,0°
Frame Lengte (horizontaal) (mm)	590	590	610	630
Balhoofdbuis Lengte (mm)	130	130	170	170
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	90,6	91	91	91
Wielbasis (mm)	1114	1114	1130	1150
Liggende achtervork lengte (mm)	470	470	470	470
Bottom Bracket Drop (mm)	70	70	70	70
Stack (mm)	663	663	663	663
Reach (mm)	392	392	394	414
Stand Over Height (mm)	588	588	540	527
Stuur breedte (mm)	660	660	660	660
Stuurpen Lengte (mm)	90	90	110	110
Cranklengte (mm)	170	170	170	170
Wielmaat	700C	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voorafkondiging wijzigen.