

ANYTOUR E+ 4 LST



SPECS

HYBRID CYKELTEKNIK	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
KONTROLLER	Single sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
VISA	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERI	Personal battery choice 500 Wh, 625 Wh or 800 Wh (suggested retail price based on 500 Wh)
LADDARE	Giant EnergyPak 4A smart charger
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Cold Night
RAM	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand
GAFFEL	SR Suntour MOBIE 34 2CR Air 60mm travel 15x100mm thru-axle
KOMPONENTER	
STYRE	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660mm
GREPPAR	Giant Comfort Ergo Microtech Plus Lock-on
STAM	Giant Contour, EVO display integrated, adjustable
SADELSTOLPE	Suspension dropper post, 30.9mm
SADEL	Selle Royal Look-In gel Moderate Wide
PEDALER	Anti-slip Platform
DRIVLINA	
VÄXLAR	Shimano Cues LinkGlide
BAKVÄXEL	Shimano Cues LinkGlide, 10-speed, Shadow+
BROMSAR	Shimano MT-200, hydraulic disc, 180mm [F/R]
BROMSSPAKAR	Shimano MT-200
KASSETT	Shimano Cues LinkGlide, 10-speed, 11-43T
KEDJA	Shimano LinkGlide
VEVPARTI	Forged alumium crank arms, 42t

HJUL	
FÄLGAR	Giant eX 2 700c Tubeless Ready Aluminium 622x21
NAV	Shimano 15x100mm [F] Shimano FH-QC400-HM [R]
EKRAR	Stainless
DÄCK	Schwalbe Marathon E Plus, 622x50, Smart DualGuard Addix E
EXTRAFUNKTIONER	KSA40 direct mount kickstand
TILLBEHÖR	
BELYSNING	Giant Recon HL50, 50 lux [F] Aegis carrier integrated tail light[R]
LÄSA	Abus Xplus Battery Lock / Abus 6950L XPlus NR
BÄRARE	MIK HD rack. System bag, basket and Aegis radar compatible
STÄNKSKÄRM/KEDJESKYDD	Aluminium Fender w/ Z-Reflector, Pistol shape

Price: 42 000,00 kr

GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	380	450	480	550
Vinkel sadelrör	73,5°	72,5°	72,0°	72,0°
Topprörets längd (mm)	570	590	610	630
Styrhuvud Längd (mm)	130	170	170	170
Vinkel styrhuvud	69,5°	69,5°	69,5°	69,5°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	90,6	90,6	90,6	90,6
Hjulbas (mm)	1106,3	1116,5	1130,1	1150,1
Kedjestagslängd (mm)	472	472	472	472
Nedre fäste Drop (mm)	70	70	70	70
Stack (mm)	625,9	663,3	663,3	663,3
Reach (mm)	384,3	380,5	394,1	414,1
Styrets bredd (mm)	660	660	660	660
Stamlängd (mm)	90	90	110	110
Vevlängd (mm)	170	170	170	170
Hjulstorlek	622X50	622X50	622X50	622X50

All specifications listed are subject to change without notice.