

ANYTOUR E+ 6 DD

GIANT



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Core, 55Nm, PedalPlus 6-sensor technology
BEDIENINGSUNIT	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	Giant EnergyPak 500Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
FRAME	
MATEN	M, L, XL
KLEUREN	Cold Iron / Black
FRAME	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 700c Frame-set, KSA40 Kickstand
VOORVORK	SR Suntour NEX E25 700C Coil 63mm travel
DEMPER	n/a
ONDERDELEN	
STUUR	Giant Contour GT, cable integrated, 30° back sweep, 31.8x660 mm
HANDVATTEN	Giant Comfort Ergo Microtech Plus Lock-on
STUURPEN	Giant Contour, EVO display integrated, adjustable
ZADELPEN	Suspension 2-bolt micro-adjustable, 30.9mm
ZADEL	Selle Royal Look-In gel
PEDALEN	Aluminum, Wellgo C211DU, PP body, anti-slip
AFMONTAGE	
SHIFTERS	Shimano Nexus 7speed Revoshift
REMMEN	Tektro HD-M275, hydraulic disc, 180mm [F], 160mm [R]
REMHENDELS	Tektro HD-M275
CASSETTE	18T
AANDRIJVING	KMC Z1e HX, e-bike optimized
CRANKSET	Aluminum, 38T
BOTTOM BRACKET	n/a

WIELSET	
VELGEN	Giant Double Wall Aluminum 622x21
NAVEN	Shimano HB-MT200 9mm QR Disc [F], Shimano Nexus 7 Disc brake [R]
SPAKEN	Stainless
BANDEN	Schwalbe Marathon 622x50 Green Guard
ACCESSOIRES	
VERLICHTING	Giant Recon HL50, 50 lux [FJAXA Juno 6-12V E-bike tail light [R]
SLOT	ABUS Xplus Battery Lock / Abus 5755L XPlus R (ART certified)
DRAGER	MIK HD rack. System bag & basket compatible
SPATBORD/ KETTINGKAST	Fully enclosed chaincase

Adviesprijs: € 3.399,00

GEOMETRIE

FRAME	M	L	XL
Zitbuis Lengte (mm)	460	480	550
Zitbuis Hoek	72,5°	72,0°	72,0°
Frame Lengte (horizontaal) (mm)	590	610	630
Balhoofdbuis Lengte (mm)	170	170	170
Balhoofdbuis Hoek	69,5°	69,5°	69,5°
Vork Sprong (mm)	44	44	44
Naloop (mm)	70	70	70
Wielbasis (mm)	1114	1128	1148
Liggende achtervork lengte (mm)	470	470	470
Bottom Bracket Drop (mm)	91	91	91
Stack (mm)	663	663	663
Reach (mm)	381	394	414
Stand Over Height (mm)	818	816	855
Stuur breedte (mm)	680	680	680
Stuurpen Lengte (mm)	90	110	110
Cranklengte (mm)	170	170	170
Wielmaat	700C	700C	700C

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder voor aankondiging wijzigen.