

ANYTOUR X E+ 0



TEKNISET TIEDOT

HYBRIDIPYÖRÄTEKNOLOGIA	
MOOTTORI	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
OHJAUSYKSIKKÖ	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
SENSORIT	Aegis Radar and Aegis Tire Checker
NÄYTTÖ	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
AKKU	Personal battery choice 500 Wh, 625 Wh or 800 Wh (suggested retail price based on 500 Wh)
LATURI	Giant EnergyPak 4A smart charger
RUNKO	
KOOT	S, M, L, XL
VÄRIT	Truffle
RUNKO	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
HAARUKKA	SR Suntour MOBIE 34 2CR Air 100mm travel, 15x100mm thru-axle
KOMONENTIT	
OHJAUSTANKO	Giant Contour Comfort Riser 31.8x690mm
GRIPIT	Giant Comfort Ergo Microtech Plus Lock-on
OHJAINKANNATIN	Giant Contour, EVO integrated, high adjustable
SATULATOLPPA	Suspension dropper post, 30.9mm
SATULA	Selle Royal Vivo Ergo Unisex
POLKIMET	Large platform pedal, 28-pins, PP cage, Steel axle
VOIMANSIIRTO	
VAIHDEVIPU	Giant RideControl Ergo4 Remote (E-Shift integrated)
JARRUT	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 203mm [F] 180mm [R]
JARRUKAHVAT	Shimano Deore, BL-M401
RATASPAKKA	Gates CDX stainless steel 22T rear sprocket
KETJUT	Gates CDX Carbon Drive 120T CenterTrack belt
KAMPISARJA	Gates CDX CenterTrack 46T front sprocket, Forged alumium crank arms

RENKAAT	
VANTEET	Giant eX25 27.5 Tubeless Ready Aluminium 584x25
NAVAT	Giant eTracker 15x100mm [F] Enviolo Trekking V3 Automatic [R]
PINNAT	stainless
RENKAAT	Schwalbe Smart Sam Plus, 584x57C (27.5 x 2.25"), DD, GreenGuard, Addix, E-50
LISÄTIEDOT	KSA40 direct mount kickstand
TARVIKKEET	
VALOT	Supernova mini 2 LDM [F] Aegis carrier integrated tail light [R]
LUKKO	ABUS Xplus Battery Lock / Abus 6950L XPlus R
TAVARATELINE	MIK HD rack. System bag, basket and Aegis radar compatible
KETJUNSUOJA	Aluminium Fender w/ Z-Reflector, Pistol shape

Suositusinta: 5 799,00 €

GEOMETRIA

RUNKO	S	M	L	XL
Satulaputken pituus (mm)	340	410	480	550
Satulaputken kulma	74,0°	73,0°	72,0°	72,0°
Vaakaputken pituus (mm)	570	590	610	630
Emäputken pituus (mm)	130	130	170	170
Emäputken kulma	69,5°	69,5°	69,5°	69,5°
Haarukan offset (mm)	44	44	44	44
Trail-mitta (mm)	85,4	85,4	85,4	85,4
Akseliväli (mm)	1120,1	1128,3	1138,1	1158,1
Takahaarukan alaputken pituus (mm)	470	470	470	470
Keskiön pudotus (mm)	50	50	50	50
Stack-mitta (mm)	624,6	624,6	662,1	662,1
Reach-mitta (mm)	390,6	398,7	394,5	414,5
Standover-mitta (mm)	411	403	396,5	419
Ohjaustangon leveys (mm)	690	690	690	690
Ohjainkannattimen pituus (mm)	90	90	110	110
Kammen pituus (mm)	170	170	170	170
Rengaskoko	584X62	584X62	584X62	584X62

Kaikki ilmoitetut tekniset tiedot voivat muuttua ilman erillistä ilmoitusta.