

ANYTOUR X E+ 0



SPECIFICATIES

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
BEDIENINGSUNIT	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
SENSOREN	Aegis Radar and Aegis Tire Checker
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
ACCU	Persoonlijke accukeuze: 500 Wh, 625 Wh of 800 Wh accu (adviesprijs op basis van 500 Wh)
LADER	Giant EnergyPak 4A smart charger
FRAME	
MATEN	S, M, L, XL
KLEUREN	Truffle
FRAME	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
VOORVORK	SR Suntour MOBIE 34 2CR Air 100mm travel, 15x100mm thru-axle
ONDERDELEN	
STUUR	Giant Contour Comfort Riser 31.8x690mm
HANDVATTEN	Giant Comfort Ergo Microtech Plus Lock-on
STUURPEN	Giant Contour, EVO integrated, high adjustable
ZADEL PEN	Suspension dropper post, 30.9mm
ZADEL	Selle Royal Vivo Ergo Unisex
PEDALEN	Large platform pedal, 28-pins, PP cage, Steel axle
AFMONTAGE	
SHIFTERS	Giant RideControl Ergo4 Remote (E-Shift integrated)
REMMEN	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 203mm [F] 180mm [R]
REMHENDELS	Shimano Deore, BL-M401
CASSETTE	Gates CDX stainless steel 22T rear sprocket
AANDRIJVING	Gates CDX Carbon Drive 120T CenterTrack belt
CRANKSET	Gates CDX CenterTrack 46T front sprocket, Forged alumium crank arms

WIELSET	
VELGEN	Giant eX25 27.5 Tubeless Ready Aluminium 584x25
NAVEN	Giant eTracker 15x100mm [F] Enviolo Trekking V3 Automatic [R]
SPAKEN	stainless
BANDEN	Schwalbe Smart Sam Plus, 584x57C (27.5 x 2.25"), DD, GreenGuard, Addix, E-50
EXTRA'S	KSA40 direct mount kickstand
ACCESSOIRES	
VERLICHTING	Supernova mini 2 LDM [F] Aegis carrier integrated tail light [R]
SLOT	ABUS Xplus Battery Lock / Abus 6950L XPlus R
DRAGER	MIK HD rack. System bag, basket and Aegis radar compatible
SPATBORD/ KETTINGKAST	Aluminium Fender w/ Z-Reflector, Pistol shape

Adviesprijs: € 5.499,00

GEOMETRIE

FRAME	S	M	L	XL
Zitbuis Lengte (mm)	340	410	480	550
Zitbuis Hoek	74,0°	73,0°	72,0°	72,0°
Frame Lengte (horizontaal) (mm)	570	590	610	630
Balhoofdbuis Lengte (mm)	130	130	170	170
Balhoofdbuis Hoek	69,5°	69,5°	69,5°	69,5°
Vork Sprong (mm)	44	44	44	44
Naloop (mm)	85,4	85,4	85,4	85,4
Wielbasis (mm)	1120,1	1128,3	1138,1	1158,1
Liggende achtervork lengte (mm)	470	470	470	470
Bottom Bracket Drop (mm)	50	50	50	50
Stack (mm)	624,6	624,6	662,1	662,1
Reach (mm)	390,6	398,7	394,5	414,5
Stand Over Height (mm)	411	403	396,5	419
Stuur breedte (mm)	690	690	690	690
Stuurpen Lengte (mm)	90	90	110	110
Cranklengte (mm)	170	170	170	170
Wielmaat	584X62	584X62	584X62	584X62

Deze specificaties zijn met de grootste zorgvuldigheid samengesteld. Specificaties, beschikbaarheid, prijzen en kleuren kunnen echter zonder vooraankondiging wijzigen.