

ANYTOUR X E+ 1



SPECS

TECNOLOGIA HÍBRIDA DE CICLISMO	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
SENSOR	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
SENSORES	Aegis Radar and Aegis Tire Checker
ECRÃ	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIA	Giant EnergyPak 800Wh
CARREGADOR	Giant EnergyPak 4A smart charger
QUADRO	
TAMANHOS	S, M, L, XL
QUADRO	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
FORQUILHA	SR Suntour MOBIE 34 2CR Air 100mm travel, 15x100mm thru-axle
COMPONENTES	
GUIADOR	Giant Contour Comfort Riser 31.8x690mm
PUNHOS	Giant Comfort Ergo Microtech Plus Lock-on
AVANÇO	Giant Contour, EVO integrated, high adjustable
ESPIGÃO DE SELIM	Suspension dropper post, 30.9mm
SELIM	Selle Royal Vivo Ergo Unisex
PEDAIS	Large platform pedal, 28-pins, PP cage, Steel axle
TRANSMISSÃO	
MANETES	Giant RideControl Ergo4 Remote (E-Shift integrated)
DESVIADOR TRASEIRO	Shimano Cues LinkGlide Di2, 11-Speed
TRAVÕES	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 180mm [F/R]
MANÍPULOS DOS TRAVÕES	Shimano Deore, BL-M401
CASSETTE	Shimano Cues LinkGlide, 11-speed, 11-45T
CORRENTE	Shimano LinkGlide
CONJUNTO PEDALEIRO	Steel narrow/wide chainring 42T, Forged alumium crank arms

RODAS	
AROS	Giant eX25 27.5 Tubeless Ready Aluminium 584x25
CUBOS	Shimano 100x15mm [F] Shimano FH-QC400-HM [R]
RAIOS	stainless
PNEUS	Schwalbe Smart Sam Plus, 584x57C (27.5 x 2.25"), DD, GreenGuard, Addix, E-50
EXTRAS	KSA40 direct mount kickstand
ACESSÓRIOS	
LUZES	Supernova mini 2 LDM [F] Aegis carrier integrated tail light [R]
CADEADO	ABUS Xplus Battery Lock / Abus 6950L XPlus NR
PORTA-BICICLETAS	MIK HD rack. System bag, basket and Aegis radar compatible
GUARDA LAMAS/PROTECTOR DE CORRENTE	Aluminium Fender w/ Z-Reflector, Pistol shape

Preço: 4 299,00 €

GEOMETRIA

QUADRO	S	M	L	XL
Comprimento do tubo do assento (mm)	340	410	480	550
Ângulo do tubo do assento	74,0°	73,0°	72,0°	72,0°
Comprimento do tubo superior (mm)	570	590	610	630
Comprimento do tubo principal (mm)	130	130	170	170
Ângulo do tubo principal	69,5°	69,5°	69,5°	69,5°
Garfo ancinho (mm)	44	44	44	44
Trilha (mm)	85,4	85,4	85,4	85,4
distância entre eixos (mm)	1120,1	1128,3	1138,1	1158,1
Comprimento Chain Stay (mm)	470	470	470	470
Suporte inferior (mm)	50	50	50	50
Pilha (mm)	624,6	624,6	662,1	662,1
Alcançar (mm)	390,6	398,7	394,5	414,5
Altura do standover (mm)	411	403	396,5	419
Largura do guidão (mm)	690	690	690	690
Comprimento da haste (mm)	90	90	110	110
Comprimento da Manivela (mm)	170	170	170	170
Tamanho da roda	584X62	584X62	584X62	584X62

Todas as especificações apresentadas estão sujeitas a alterações sem aviso prévio.