

ANYTOUR X E+ 2



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
CONTROLLER	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERY	Giant EnergyPak 625Wh
CHARGER	Giant EnergyPak 4A smart charger
FRAME	
SIZES	S, M, L, XL
FRAME	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
FORK	SR Suntour MOBIE 34 2CR Air 100mm travel, 15x100mm thru-axle
COMPONENTS	
HANDLEBAR	Giant Contour Comfort Riser 31.8x690mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
STEM	Giant Contour, EVO integrated, high adjustable
SEATPOST	Suspension dropper post, 30.9mm
SADDLE	Selle Royal Vivo Ergo Unisex
PEDALS	Large platform pedal, 28-pins, PP cage, Steel axle
DRIVETRAIN	
SHIFTERS	Microshift 5-speed trigger shifter
BRAKES	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 180mm [F/R]
BRAKE LEVERS	Shimano Deore, BL-M401
CASSETTE	Gates CDX stainless steel 32T rear sprocket
CHAIN	Gates CDX Carbon Drive 125T CenterTrack belt
CRANKSET	Gates CDX CenterTrack 46T front sprocket, Forged aluminium crank arms

WHEELS	
RIMS	Giant eX25 27.5 Tubeless Ready Aluminium 584x25
HUBS	Shimano 100x15mm [F] Shimano Nexus E5 Disc brake [R]
SPOKES	stainless
TIRES	Schwalbe Smart Sam Plus, 584x57C (27.5 x 2.25"), DD, GreenGuard, Addix, E-50
EXTRAS	KSA40 direct mount kickstand
ACCESSORIES	
LIGHTING	Giant Recon HL50, 50 lux [F] Aegis carrier integrated tail light[R]
LOCK	ABUS Xplus Battery Lock / Abus 6950L XPlus NR
CARRIER	MIK HD rack. System bag, basket and Aegis radar compatible
FENDER/CHAINGUARD	Aluminium Fender w/ Z-Reflector, Pistol shape

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	340	410	480	550
Seat Tube Angle	74,0°	73,0°	72,0°	72,0°
Top Tube Length (mm)	570	590	610	630
Head Tube Length (mm)	130	130	170	170
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	85,4	85,4	85,4	85,4
Wheelbase (mm)	1120,1	1128,3	1138,1	1158,1
Chain Stay Length (mm)	470	470	470	470
Bottom Bracket Drop (mm)	50	50	50	50
Stack (mm)	624,6	624,6	662,1	662,1
Reach (mm)	390,6	398,7	394,5	414,5
Stand Over Height (mm)	411	403	396,5	419
Handlebar Width (mm)	690	690	690	690
Stem Length (mm)	90	90	110	110
Crank Length (mm)	170	170	170	170
Wheel Size	584X62	584X62	584X62	584X62

All specifications listed are subject to change without notice.