

ANYTOUR X E+ 2



SPECIFIKACIJE

HIBRIDNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
SENSOR	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZ	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIJA	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIČINE	S, M, L, XL
BOJE	Black Diamond / Black, Sangria / Black
OKVIR	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27.5" Frame-set, KSA40 Kickstand
VILICA	SR Suntour XCR32 ATB LOR 27.5" Air 100mm
AMORTIZER	n/a
KOMPONENTE	
VOLAN	Giant Contour Comfort Riser 31.8x690mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
LULA VOLANA	Giant Contour, EVO integrated, high adjustable
CIJEV SJEDALA	Suspension dropper post, 30.9mm
SJEDALO	Selle Royal Vivo Ergo Unisex
PEDALE	VP VPES37, PP platform / Anti-slip
POGON	
RUČICE MJENJAČA	Shimano E5, 5-speed Revoshift
PREDNJI MJENJAČ	n/a
STRAŽNJI MJENJAČ	n/a
KOČNICE	Shimano Deore, BR-MT410, hydraulic disc, 180mm
RUČICE KOČNICA	Shimano Deore
KAZETA	Gates CDXtm stainless steel 32T rear sprocket
LANAC	Gates CDXtm Carbon Drive 125T CenterTrack belt
POGON	Gates CDXtm CenterTrack 46T front sprocket
OSOVINA POGONA (BB)	n/a

KOTAČI	
OBRUČI	Giant eX25, Tubeless Ready, 584x25 Aluminium
NABE	Shimano HB-MT200 100x9mm QR Disc [F], Shimano Nexus E5 Disc brake [R]
ŽBICE	Stainless
GUME	Schwalbe Smart Sam Plus 57-584 (27.5 x 2.25"), DD, GreenGuard, ADDIX, E-50
DODACI	KSA40 direct mount kickstand
DODACI	
SVJETLA	Giant Recon HL50, 50 lux [F] AXA Juno 6-12V E-bike tail light [R]
LOKOTI	MIK HD rack. System bag & basket compatible

GEOMETRIJA

OKVIR	S	M	L	XL
Dužina cijevi sjedala (mm)	340	410	480	550
Kut cijevi sjedala	74,0°	73,0°	72,0°	72,0°
Dužina gornje cijevi (mm)	570	590	610	630
Dužina prednje cijevi (mm)	130	130	170	170
Kut vilice	69,5°	69,5°	69,5°	69,5°
Zakrivljenost vilice (offset) (mm)	44	44	44	44
Staza (mm)	87	87	87	87
Međuosovinski razmak kotača (mm)	1120	1128	1138	1158
Dužina od osovine pogona do osovine zadnjeg kotača (CS) (mm)	470	470	470	470
Položaj osovine pogona (mm)	50	50	50	50
Vertikalna dužina od osovine pogona do glave okvira (stack) (mm)	625	625	662	662
Horizontalna dužina od osovine pogona do glave okvira (reach) (mm)	391	399	395	415
Prekoračna visina (mm)	592	564	524	488
Širina volana (mm)	690	690	690	690
Dužina lule volana (mm)	90	90	110	110
Dužina poluge pedale (mm)	170	170	170	170
Veličina kotača	27.5"	27.5"	27.5"	27.5"

Sve navedene specifikacije podložne su promjeni bez prethodne najave.