

ANYTOUR X E+ 2

GIANT



SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
SENSOR	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERY	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
CADRU	
MARIMI	S, M, L, XL
CULORI	Black Diamond / Black, Sangria / Black
CADRU	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27.5" Frame-set, KSA40 Kickstand
FURCA	SR Suntour XCR32 ATB LOR 27.5" Air 100mm
SOC	n/a
COMPONENTE	
GHIDON	Giant Contour Comfort Riser 31.8x690mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
PIPA	Giant Contour, EVO integrated, high adjustable
TIJA SA	Suspension dropper post, 30.9mm
SA	Selle Royal Vivo Ergo Unisex
PEDALE	VP VPES37, PP platform / Anti-slip
SISTEMUL DE SCHIMBARE A VITEZELOR	
MANETE SCHIMBATOR	Shimano E5, 5-speed Revoshift
SCHIMBATOR FATA	n/a
SCHIMBATOR SPATE	n/a
FRANE	Shimano Deore, BR-MT410, hydraulic disc, 180mm
MANETE FRANA	Shimano Deore
PINIOANE	Gates CDXtm stainless steel 32T rear sprocket
LANT	Gates CDXtm Carbon Drive 125T CenterTrack belt
ANGRENAJ	Gates CDXtm CenterTrack 46T front sprocket
BOTTOM BRACKET	n/a

ROTI	
JANTE	Giant eX25, Tubeless Ready, 584x25 Aluminium
BUTUCI	Shimano HB-MT200 100x9mm QR Disc [F], Shimano Nexus E5 Disc brake [R]
SPITE	Stainless
ANVELOPE	Schwalbe Smart Sam Plus 57-584 (27.5 x 2.25"), DD, GreenGuard, ADDIX, E-50
EXTRAS	KSA40 direct mount kickstand
ACCESSORIES	
LIGHTING	Giant Recon HL50, 50 lux [F] AXA Juno 6-12V E-bike tail light [R]
LOCK	MIK HD rack. System bag & basket compatible

GEOMETRIE

CADRU	S	M	L	XL
Seat Tube Length (mm)	340	410	480	550
Seat Tube Angle	74,0°	73,0°	72,0°	72,0°
Top Tube Length (mm)	570	590	610	630
Head Tube Length (mm)	130	130	170	170
Head Tube Angle	69,5°	69,5°	69,5°	69,5°
Fork Rake (mm)	44	44	44	44
Trail (mm)	87	87	87	87
Wheelbase (mm)	1120	1128	1138	1158
Chain Stay Length (mm)	470	470	470	470
Bottom Bracket Drop (mm)	50	50	50	50
Stack (mm)	625	625	662	662
Reach (mm)	391	399	395	415
Stand Over Height (mm)	592	564	524	488
Handlebar Width (mm)	690	690	690	690
Stem Length (mm)	90	90	110	110
Crank Length (mm)	170	170	170	170
Wheel Size	27.5"	27.5"	27.5"	27.5"

Toate specificatiile enumerate se pot schimba fara notificare prealabila.