



SPECIFIKACIJE

HIBRIDNA GONILNA TEHNOLOGIJA	
MOTOR	Giant SyncDrive Sport2, 75Nm, PedalPlus 6-sensor technology
TIPALO	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
PRIKAZOVALNIK	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATERIJA	Giant EnergyPak 625Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production
CHARGER	Giant EnergyPak 4A smart charger compact, 60% charge in 2:30h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
OKVIR	
VELIKOSTI	S, M, L, XL
BARVE	Black Diamond / Black, Sangria / Black
OKVIR	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
VILICE	SR Suntour XCR32 ATB LOR 27.5" Air 100mm
AMORTIZER	n/a
KOMPONENTE	
KRMILO	Giant Contour Comfort Riser 31.8x690mm
GRIPS	Giant Comfort Ergo Microtech Plus Lock-on
OPORA KRMILA	Giant Contour, EVO integrated, high adjustable
OPORA SEDEŽA	Suspension dropper post, 30.9mm
SEDEŽ	Selle Royal Vivo Ergo Unisex
PEDALA	VP VPES37, PP platform / Anti-slip
POGON	
PRESTAVNE ROČICE	Shimano E5, 5-speed Revoshift
PREDNJI MENJALNIK	n/a
ZADNJI MENJALNIK	n/a
ZAVORE	Shimano Deore, BR-MT410, hydraulic disc, 180mm
ZAVORNE ROČICE	Shimano Deore
VERIŽNIK	Gates CDXtm stainless steel 32T rear sprocket
VERIGA	Gates CDXtm Carbon Drive 125T CenterTrack belt
GONILKE Z VERIŽNIKI	Gates CDXtm CenterTrack 46T front sprocket
BOTTOM BRACKET	n/a

OBROČNIKI	
OBROČI	Giant eX25, Tubeless Ready, 584x25 Aluminium
PESTA	Shimano HB-MT200 100x9mm QR Disc [F], Shimano Nexus E5 Disc brake [R]
NAPERE	Stainless
PLAŠČI	Schwalbe Smart Sam Plus 57-584 (27.5 x 2.25"), DD, GreenGuard, ADDIX, E-50
DODATKI	KSA40 direct mount kickstand
DODATNA OPREMA	
SVETILA	Giant Recon HL50, 50 lux [F] AXA Juno 6-12V E-bike tail light [R]
KLJUČAVNICA	MIK HD rack. System bag & basket compatible

GEOMETRIJA

OKVIR	S	M	L	XL
Dolžina sedežne cevi (mm)	340	410	480	550
Kot sedežne cevi	74,0°	73,0°	72,0°	72,0°
Top Tube Length (mm)	570	590	610	630
Višina glave okvirja (mm)	130	130	170	170
Krmilni kot	69,5°	69,5°	69,5°	69,5°
Zamik vpetja osi (mm)	44	44	44	44
Trail (mm)	87	87	87	87
Medosna razdalja (mm)	1120	1128	1138	1158
Dolžina cevi ob verigi (mm)	470	470	470	470
Bottom Bracket Drop (mm)	50	50	50	50
Oddaljenost zgornje cevi od gonilne osi (mm)	625	625	662	662
Doseg (mm)	391	399	395	415
Višina zgornje cevi (mm)	592	564	524	488
Širina krmila (mm)	690	690	690	690
Dolžina opore krmila (mm)	90	90	110	110
Dolžina gonilke (mm)	170	170	170	170
Velikost obročnikov	27.5"	27.5"	27.5"	27.5"

Vse navedene specifikacije se lahko spremenijo brez obvestila.