ANYTOUR X E+ 2



SPECS

E+ SYSTEM	
MOTOR	Giant SyncDrive Sport3 85Nm, PedalPlus 6-Sensor technology
KONTROLLER	Dual sided RideControl Ergo 4 w/ RideControl Go2 turn-on button
VISA	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERI	Personal battery choice 500 Wh, 625 Wh or 800 Wh (suggested retail price based on 500 Wh)
LADDARE	Giant EnergyPak 4A smart charger
RAM	
STORLEKAR	S, M, L, XL
FÄRGER	Abyss Black
RAM	ALUXX SL aluminum, Integrated battery design, Headset integrated cable routing, M10 Trailer Mount, 27,5" Frame-set, KSA40 Kickstand
GAFFEL	SR Suntour MOBIE 34 2CR Air 100mm travel, 15x100mm thru-axle
KOMPONENTER	
STYRE	Giant Contour Comfort Riser 31.8x690mm
GREPPAR	Giant Comfort Ergo Microtech Plus Lock-on
STAM	Giant Contour, EVO integrated, high adjustable
SADELSTOLPE	Suspension dropper post, 30.9mm
SADEL	Selle Royal Vivo Ergo Unisex
PEDALER	Large platform pedal, 28-pins, PP cage, Steel axle
DRIVLINA	
VÄXLAR	Microshift 5-speed trigger shifter
BROMSAR	Shimano Deore, BR-M420, hydraulic disc, 4-piston, 180mm [F/R]
BROMSSPAKAR	Shimano Deore, BL-M401
KASSETT	Gates CDX stainless steel 32T rear sprocket
KEDJA	Gates CDX Carbon Drive 125T CenterTrack belt
VEVPARTI	Gates CDX CenterTrack 46T front sprocket, Forged alumium crank arms

HJUL	
FÄLGAR	Giant eX25 27.5 Tubeless Ready Aluminium 584x25
NAV	Shimano HB-MT200 9mm QR disc [F] Shimano Nexus E5 disc brake [R]
EKRAR	stainless
DÄCK	Schwalbe Smart Sam Plus, 584x57C (27.5 x 2.25"), DD, GreenGuard, Addix, E-50
EXTRAFUNKTIONER	KSA40 direct mount kickstand
TILLBEHÖR	
BELYSNING	Giant Recon HL50, 50 lux [F] Aegis carrier integrated tail light[R]
LÅSA	ABUS Xplus Battery Lock / Abus 6950L XPlus R
BÄRARE	MIK HD rack. System bag, basket and Aegis radar compatible
STÄNKSKÄRM/KEDJESKYDD	Aluminium Fender w/ Z-Reflector

Price: 51 000,00 kr

GEOMETRY

RAM	S	M	L	XL
Längd sadelrör (mm)	340	410	480	550
Vinkel sadelrör	74,0°	73,0°	72,0°	72,0°
Topprörets längd (mm)	570	590	610	630
Styrhuvud Längd (mm)	130	130	170	170
Vinkel styrhuvud	69,5°	69,5°	69,5°	69,5°
Gaffelvinkel (mm)	44	44	44	44
Spår (mm)	85,4	85,4	85,4	85,4
Hjulbas (mm)	1120,1	1128,3	1138,1	1158,1
Kedjestagslängd (mm)	470	470	470	470
Nedre fäste Drop (mm)	50	50	50	50
Stack (mm)	624,6	624,6	662,1	662,1
Reach (mm)	390,6	398,7	394,5	414,5
Stå över höjden (mm)	411	403	396,5	419
Styrets bredd (mm)	690	690	690	690
Stamlängd (mm)	90	90	110	110
Vevlängd (mm)	170	170	170	170
Hjulstorlek	584X62	584X62	584X62	584X62

All specifications listed are subject to change without notice.